

CLEANING GUIDE For Use With





THERMOPLASTIC/ACRYLIC FOOD SHIELD PANELS

STANDARD CLEANING RECOMMENDATION

For general purpose cleaning, wash Vivak PETG sheet siwth a mild (non-abrasive) soap solution and lukewarm water.

Make sure to use a lint-free cloth to avoid scratching the sheet.

To prevent water spotting, thoroughly dry with chamois or cellulose sponge.

SUGGESTED CLEANING AGENTS

The following cleaning agents were found to be compatible with Vivak PETG sheet under laboratory conditions.

Soaps/Detergents:

- Joy (trademark of Procter & Gamble)
- Mr. Clean (trademark of Procter & Gamble)
- Fantastik (trademark of Texize division of Norton Norwich Products Inc.)
- Formula 409 (trademark of the Clorox Company)

Organic Solvents:

- Kerosene
- Isopropyl Alcohol
- Methanol
- Naphtha

*NOTE - All residual organic solvents should be removed with a secondary rinse. Keep duration of exposure to solvents at a minimum.

GRAFFITI REMOVAL

Butyl cellosolve may be used to remove paint from Vivak PETG.

STICKY SUBSTANCE REMOVAL

To remove old stickers or labels, VM&P Naphtha or kerosene are often effective.

www.advancetabco.com

1-800-645-3166 • customer@advancetabco.com

National Manufacturing & Distribution: Georgia² • Tennessee • Texas² • Mississippi • New York • South Carolina • Nevada • Kentucky

