

**ADJUST-A-FIT® PLATE DISPENSER CABINETS – HEATED/NON-HEATED | STAINLESS STEEL**

*Hold a variety of different size plates in the same cabinet for ultimate award-winning flexibility.*

- Choose up to four plate stacks to conveniently hold varying sizes and number of plates
- Each heated dispenser features its own thermostatic control to manage and adjust temperature
- Adjust-a-fit diameter hand adjustment of 3 1/4" (83) allows flexibility for varying dish sizes
- Adjusting height level is easy and convenient.
- Easy glide design is non-stick for smooth operation
- All 4" swivel casters, 2 with brake, allow easy maneuverability.
- All welded construction increases durability
- Stainless steel material is easy to clean and sanitize
- Dispensers have 25" (635) stacking height capacity



**1. Height Adjustment** – Simply detach or attach springs to adjust tension for the height level you desire.  
**2. & 3. Adjust-a-Fit® Size Adjustment** – Easily re-position and lock the dish guides with a turn of the wrist. No tools necessary!



**FACTORY INSTALLED OPTIONS:**

- Bottom perimeter bumper
- 8" (203) one piece vertical handle (except 4 stack)

**ACCESSORIES (PAGE 79):**

- Stainless Steel Dish Covers
- 12" (305) Dispenser Tray available for Models 935, 937 972 and 975



One piece vertical handle

**ELECTRICAL SPECIFICATIONS**

Model	W	A	V
Model #917	600 W	5.0 A	120 V
Model #937	900 W	7.5 A	120 V
Model #965	1350 W	11.3 A	120 V
Model #927	900 W	7.5 A	120 V
Model #975	1350 W	11.3 A	120 V
Model #929	1800 W	15.0 A	120 V

208 / 240V, 60 Hz; 220V, 50 Hz also available, please specify.

Freight Class: **92.5**  
Ships in: **4** days or less!



Model	Accommodates Plate Sizes	Overall Size				Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m³)	Case Cube Cu. ft. (m³)
		W	L	H	(W L H)			
<b>2 Stack - Non-Heated Models</b>								
905	2-3/4" to 6" (70 to 152)	17-1/4"	26-1/8"	39-1/8"	(438 664 994)	85 (38.6)	12.9 (.4)	12.9 (.4)
915	4-1/4" to 7-1/2" (108 to 191)	17-1/4"	26-1/8"	39-1/8"	(438 664 994)	92 (41.7)	12.9 (.4)	12.9 (.4)
925	6-1/2" to 9-3/4" (165 to 248)	17-1/4"	30-5/8"	39-1/8"	(438 778 994)	100 (45.4)	14.9 (.4)	14.9 (.4)
935	8-3/4" to 12" (222 to 305)	19-1/2"	35-1/8"	39-1/8"	(495 892 994)	115 (52.2)	18.9 (.5)	18.9 (.5)
<b>3 Stack - Non-Heated Models</b>								
942	2-3/4" to 6" (70 to 152)	17-3/16"	38-5/16"	39-1/8"	(437 973 994)	112 (50.8)	18.4 (.5)	18.4 (.5)
952	4-1/4" to 7-1/2" ((108 to 191)	17-3/16"	38-5/16"	39-1/8"	(437 973 994)	120 (54.4)	18.4 (.5)	18.4 (.5)
962	6-1/2" to 9-3/4" (165 to 248)	17-3/16"	45-1/16"	39-1/8"	(437 1145 994)	132 (59.9)	22.2 (.6)	22.2 (.6)
972	8-3/4" to 12" (222 to 305)	19-3/16"	51-13/16"	39-1/8"	(487 1316 994)	152 (69)	27.1 (.8)	27.1 (.8)
<b>4 Stack - Non-Heated Models</b>								
908	2-3/4" to 6" (70 to 152)	30-5/8"	30-5/8"	39-1/8"	(778 778 994)	127 (57.6)	19.5 (.5)	19.5 (.5)
918	4-1/4" to 7-1/2" ((108 to 191)	30-5/8"	30-5/8"	39-1/8"	(778 778 994)	131 (59.4)	19.5 (.5)	19.5 (.5)
928	6-1/2" to 9-3/4" (165 to 248)	30-5/8"	30-5/8"	39-1/8"	(778 778 994)	153 (69.4)	25.8 (.7)	25.8 (.7)
<b>2 Stack - Heated Model</b>								
917	4-1/4" to 7-1/2" (108 to 191)	17-1/4"	30-5/8"	39-1/8"	(438 778 994)	113 (51.3)	14.9 (.4)	14.9 (.4)
927	6-1/2" to 9-3/4" (165 to 248)	17-1/4"	30-5/8"	39-1/8"	(438 778 994)	126 (57.2)	14.9 (.4)	14.9 (.4)
937	8-3/4" to 12" (222 to 305)	19-1/2"	35-1/8"	39-1/8"	(495 892 994)	142 (64.4)	18.9 (.5)	18.9 (.5)
<b>3 Stack - Heated Models</b>								
955	4-1/4" to 7-1/2" (108 to 191)	17-3/16"	45"	39-1/8"	(437 1145 994)	151 (68.5)	21.9 (.6)	21.9 (.6)
965	6-1/2" to 9-3/4" (165 to 248)	17-3/16"	45"	39-1/8"	(437 1145 994)	167 (75.8)	21.9 (.6)	21.9 (.6)
975	8-3/4" to 12" (222 to 305)	19-3/16"	51-13/16"	39-1/8"	(487 1316 994)	175 (79.4)	28.1 (.8)	28.1 (.8)
<b>4 Stack - Heated Model</b>								
919	4-1/4" to 7-1/2" (108 to 191)	30-5/8"	30-5/8"	39-1/8"	(778 778 994)	190 (86.2)	25.8 (.7)	25.8 (.7)
929	6-1/2" to 9-3/4" (165 to 248)	30-5/8"	30-5/8"	39-1/8"	(778 778 994)	196 (88.9)	25.8 (.7)	25.8 (.7)

Measurements in ( ) denote metric millimeters, unless otherwise specified. Lake-Glide® Casters: 4" (102) - All swivel, 2 ea. w/brake, extra-load. Heated Models include 6' (1829) coiled cord with 5-15P NEMA (except Model 929 which includes 5-20P) plug for 120 V.) All models 25" (635) plate stacking capacity per dispenser tube.