

HEATED PELLET DISPENSERS | STAINLESS STEEL

Evenly heat pellets before serving to help maintain safe food temps throughout your meal delivery service.

- Convection forced air heating ensures even heat transfer to all pellets to ensure each pellet will maintain safe food temperatures
- Unique lid design holds in heat without gaskets, so pellets maintain heat
- Dispenser cabinet is fully insulated to conserve energy
- Single heat control for 2 or 3 dispensers in a single compartment
- Dispensers are self-lubricating for smooth operation
- Push handle for more control during transportation
- All 5" swivel casters, 2 with brake, allow easy maneuverability
- Stainless steel construction increases durability, easy to clean and sanitize
- Each dispenser accommodates a 27" stack of pellets with a diameter of 7 to 10 1/4"
- Handles both metal and plastic pellet systems for added flexibility

DUO-THERM™ HEATED PELLET and PLATE DISPENSERS | STAINLESS STEEL

The convenience of heating both plates and pellets in one unit, where separate plate and pellet units are not practical – to save time and energy.

- Model 7500 heats pellets and plates in one mobile unit with the same innovative features and construction of Lakeside's convection heated dispensers
- Convection forced air heating ensures even heat transfer to all pellets and plates
- Two heated compartments are independently controlled for flexibility
- Adjustable hi-temp shut-off control for safety

ELECTRICAL SPECIFICATIONS			
Model #7500	3200 W 60 Hz	17.2 A Single Phase	208/220 V
Model #7501	3200 W 60 Hz	16.3 A Single Phase	208/220 V
Model #7502	3200 W 60 Hz	16.3 A Single Phase	208/220 V



Dispensers are removable for convenient cleaning and adjustments.



Model #7502 has 3 dispensers and a single control for heating pellets.

Model #7500



Model 7500 safely heats both pellets and plates in one mobile unit.



Freight Class: **125**
Ships in: **7** days or less!

Model	# of Dispensers	Overall Size			Caster Type	Caster Dia.	Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m ³)
		W	D	H				
7500 Duo-Therm	2	36" (914)	24" (610)	42-3/4" (1086)	4 swivel 2 w/ brake	5" (127)	285 (129.3)	32.7 (.93)
7501 1 Control	2	33-3/8" (849)	23-3/4" (603)	42-3/4" (1086)	4 swivel 2 w/ brake	5" (127)	260 (117.9)	24.0 (.68)
7502 1 Control	3	43-7/16" (1103)	23-3/4" (603)	42-3/4" (1086)	4 swivel 2 w/ brake	5" (127)	300 (136.1)	31.1 (.88)

Measurements in () denote metric millimeters, unless otherwise specified. 50 Hz power also available, please specify. Includes 10' (3048) power cord.

