



Brema Ice Machines add a touch of elegance to your establishment. Known and trusted in the industry for high-quality construction and consistent production, they are the most reliable choice for all your ice production needs.

Ice Flakes



Brema Ice Flake Machines are used in retail, fish and seafood, and therapeutic sectors for chilled displays and presentations. The auger and ice breaker work together to create irregular shapes in a continuous fashion. The simplicity of the production process ensures cost-effective operation.



Granular Ice, 80-82% Dry

Standard Features



1L water = 1kg ice



AISI 304 Stainless steel evaporator



Air cooling system



Easy cleanable internal rounded surfaces



Dust-proof water basin



RoHS Free



Electromechanical operation



ON/OFF switch



Automatic water charge



HFC Free
HC R290 Refrigerant Gas



GB Series

Standard Features Included



Adjustable stainless steel feet



HCFC-Free insulated storage



Retractable insulated door



GB903A HC



GB1504A HC

Brema Ice Machine Cleaner

For use with Brema Ice Machines to completely descale and clean interior and exterior surfaces and components. Colorless and odorless, powdered agent. Sold separately.

G Series

Standard Features Included



1 m³ = 550 kg of ice



Rotation sensor on low speed shaft



G160A HC



G280A HC




BIN110



BIN200

GB903A HC




Adjustable feet 4 5/16" – 5 14/16"

115V, 450W, 4.5A
—
253 lbs
209 lbs
66 lbs
26" x 19.5" x 31.5"
148 lbs
29" x 30.75" x 40"
167.5 lbs

Power
Compatible With
Production/24h*
Production/24h**
Bin Capacity
Dimensions (L x W x H)
Net weight
Ship Dim. (L x W x H)
Ship weight

- ① WATER IN: 3 14/16" – 6 4/16" – 3/4"
- ② WATER OUT: 1 14/16" – 5 15/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 7/16" – 9 1/16"

GB1504A HC




Adjustable feet 4 5/16" – 5 14/16"

115V, 680W, 15A
—
368 lbs
335 lbs
88 lbs
27" x 29" x 36"
187 lbs
29" x 30.75" x 46.5"
209 lbs

- ① WATER IN: 4 2/16" – 7 3/16" – 3/4"
- ② WATER OUT: 2 1/16" – 6 14/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 3 10/16" – 10"

G160A HC




- ① WATER IN: 3 3/16" – 4 12/16" – 3/4"
- ② WATER OUT: 18 14/16" – 2 9/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 2 11/16" – 11 7/16"

115V, 665W, 5.8A
BIN110
380 lbs
368 lbs
—
22.4" x 22" x 23.6"
139 lbs
25.4" x 25.4" x 32"
163 lbs

Power
Compatible With
Production/24h*
Production/24h**
Bin Capacity
Dimensions (L x W x H)
Net weight
Ship Dim. (L x W x H)
Ship weight

G280A HC




- ① WATER IN: 3 3/16" – 4 12/16" – 3/4"
- ② WATER OUT: 18 14/16" – 2 9/16" – 15/16"
- ③ ELECTRICAL CONNECTIONS: 2 11/16" – 11 7/16"

120V, 1050W, 8.5A
BIN200
668 lbs
529 lbs
—
22" x 22" x 27.5"
183 lbs
25.5" x 25.5" x 36"
205 lbs

Power
Compatible With
Production/24h*
Production/24h**
Bin Capacity
Dimensions (L x W x H)
Net weight
Ship Dim. (L x W x H)
Ship weight

BIN110




Adjustable feet 3 15/16" – 6 15/16"

—
G160A HC
—
—
220 lbs
32" x 22" x 39.5"
117 lbs
34.5" x 24.5" x 46.25"
143 lbs

Power
Compatible With
Production/24h*
Production/24h**
Bin Capacity
Dimensions (L x W x H)
Net weight
Ship Dim. (L x W x H)
Ship weight

BIN200



Adjustable feet 3 15/16" – 6 15/16"

—
G280A HC
—
—
440 lbs
31" x 34" x 39.5"
163 lbs
33" x 36.25" x 47.5"
205 lbs

Power
Compatible With
Production/24h*
Production/24h**
Bin Capacity
Dimensions (L x W x H)
Net weight
Ship Dim. (L x W x H)
Ship weight

*Ambient Temperature 21°C (70°F) / Water 10°C (50°F)
 **Ambient Temperature 32°C (90°F) / Water 21°C (70°F)



Warranty
 3 years parts & labor,
 5 years on the compressor