

VLT650ADA



32" x 23.63" x 23.5" (H x W x D)

Built-in undercounter ADA compliant laboratory freezer capable of -35° C (-31° F) operation

Highlights:

Commercially listed to NSF-7 standards and meets UL-471

Capable of operating at -35° C

Precise temperature control with a digital thermostat

Product Features:

| | |
|--------------------------------|--|
| Commercially approved | UL-S listed to NSF-7 commercial standards and meets UL commercial standard 471 |
| ADA compliant | 32" height allows installation under lower ADA compliant counters |
| -35° C (-31° F) capable | Low temperature operation ideal for vaccines, pharmaceuticals, and other sensitive materials |
| Built-in capable | Front-breathing system allows the unit to be used built-in |
| Factory installed lock | Keyed lock offers convenient security |
| Three slide-out drawers | Conveniently organize your items while keeping the temperature stable when the door is opened |
| Digital thermostat | Electronic controls for precise temperature management |
| Alarm with temperature display | Audible alarm sounds to warn of temperature variations with a digital readout on the thermometer to provide the interior temperature |
| Manual defrost | Static cooling system with manual defrost operation |

VLT650ADA Specifications:

| Overview | |
|----------------------------|--------------------|
| Height of Cabinet | 32.0" (81 cm) |
| Width | 23.63" (60 cm) |
| Depth | 23.5" (60 cm) |
| Capacity | 3.5 cu.ft. (99 L) |
| Defrost Type | Manual |
| Door | White |
| Cabinet | White |
| US Electrical Safety | UL |
| Canadian Electrical Safety | ULC |
| Sanitation | UL-S |
| Voltage/Frequency | 115 V AC/60 Hz |
| Shipping Weight | 135.0 lbs. (61 kg) |
| Parts & Labor Warranty | 1 Year |
| Compressor Warranty | 5 Years |
| Freezer | |
| Door Swing | RHD |
| Reversible | Factory Reversible |
| Thermostat Type | Digital |
| Refrigerant Type | R134a |
| Refrigerant Amount | 2.76 oz. |
| Interior Drawers | Yes |
| Drawers Qty | 3 |

