# Plate Casters for Commercial Equipment



# 5" Heavy-Duty Universal Square Plate Casters w/Brakes

- Grease-resistant, non-marking, polyurethane wheels with brakes
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- 500 lb (227 kg) capacity per wheel for heavy-duty applications
- Temp. range: 14°F to 212°F (-10°C to 100°C)

| Item #   | Description   | Capacity per Caster | Case |
|----------|---|---------------------|------|
| FPCST5HD | Set of 4 - 5" (12.7 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes | 500 lbs (226 kg)    | 4    |
| FPCST5HD | Individual 5" (12.7 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes | 500 lbs (226 kg)    | 4    |

### 2" Universal Low-Profile Plate Casters w/Brakes

- 2" (5.1 cm) wheels with brakes
- Adds 3" (7.6 cm) to overall height
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- 200 lb. (91 kg) capacity per wheel
- Temp. range: 14°F to 212°F (-10°C to 100°C)

| Item #  | Description   | Capacity per Caster | Case |
|---------|---|---------------------|------|
| FPCS352 | Set of 4 - 2" (5.1 cm) Universal Plate Casters w/Brakes | 250 lbs (113 kg)    | 4    |
|         | 3 1/2" (8.9 x 8.9 cm) Square Plate                      |                     |      |

# 3" or 5" Square Plate Casters w/Brakes

- Grease-resistant, non-marking, polyurethane wheels with brakes
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- Temp. range: 14°F to 212°F (-10°C to 100°C)

| ltem # | Description   | Capacity per Caster | Case |  |
|--------|---|---------------------|------|--|
| FPCST3 | Set of 4 - 3" (7.6 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes  | 250 lbs (113 kg)    | 4    |  |
| FPCST5 | Set of 4 - 5" (12.7 cm) Universal Casters, 4" (10.2 cm) Square Plate w/Brakes | 250 lbs (113 kg)    | 4    |  |

## 5" Universal Square Plate Casters

- Grease-resistant, non-marking, polyurethane wheels with brakes
- Stainless steel mounting plate with multiple bolt holes to fit an assortment of equipment
- Temp. range: 14°F to 212°F (-10°C to 100°C)

| Item #   | Description   | Capacity per Caster | Case |
|----------|---|---------------------|------|
| FPCST355 | Set of 4 - 5" (12.7 cm) Universal Casters w/Brakes 3 1/2" (8.9 cm) Square Plate | 250 lbs (113 kg)    | 4    |

# 5" Universal Rectangular Plate Casters w/Brakes

- Grease-resistant, non-marking, polyurethane wheels with brakes
- 250 lb. (113 kg) capacity per wheel
- Temp. range: 14°F to 212°F (-10°C to 100°C)

| Item #    | Description  | Capacity per Caster | Case |
|-----------|--|---------------------|------|
| FPCST2X35 | Set of $4-5$ " (12.7 cm) Universal Casters w/Brakes $2^3/8$ " x $3^5/8$ " (6.0 x 9.2 cm) Rectangle Plate | 50 lbs (113 kg)     | 4    |

## 3" Universal Rectangular Plate Casters\*

- Polyolefin wheel casters, 2 each swivel and 2 each swivel with brakes
- 250 lb. (113 kg) capacity per wheel
- Temp. range: -20°F to +180°F (-28.9°C to +82.2°C)

| Item #    | Description  | Capacity per Caster | Case |
|-----------|--|---------------------|------|
| FPCST2X33 | Set of 4 - 3" (7.6 cm) Universal Casters w/Brakes 2 <sup>3</sup> /8" x 3 <sup>5</sup> /8" (6.0 x 9.2 cm) Rectangle Plate | 250 lbs (113 kg)    | 4    |

### **Plate Casters**

These casters' stainless steel mounting plates feature multiple bolt holes to fit an assortment of equipment.















\*Fits Entree®

**Economy Fryers**