

Temperature and Humidity Monitoring



N2011



N2012



N2013



N2014

Diligence EV Product Line

N2011	Internal temperature sensor with LCD
N2012	Internal temperature sensor and up to 4 external sensors with N2000 Box with LCD
N2013	Single temperature and humidity alarm with LCD
N2014	Thermocouple logger with range of -328°F to +2502°F with N2000ADP/K and appropriate probes with LCD
N2000CRUSB	Communications interface with USB connection
N2000BOX	Multi-link box to connect up to 4 probes to N2012
N2000ADP/K	Type K Adaptor to connect up to 3 thermocouple probes to N2014
N2000ADP/T	Type T Adaptor to connect up to 3 thermocouple probes to N2014
EVSW	Standard software
EVSWPRO	Software for use with 21CFR Part II
PX31L	Penetration probe, 1m long with 10cm stem for N2012
PK31L	Penetration probe, 1m long with stem for N2014

EVt2 Temperature Logger



Multi-Use Logger makes it easy to comply with USDA and HACCP requirements by monitoring the temperatures of meat, seafood and produce shipments 24/7.

- Review maximum, minimum and average trip temperatures plus total time in alarm, right on the screen
- Accept or reject a shipment in seconds
- Download data to a PC for permanent HACCP records
- Single button starts/stops logging
- Up to 3,000 readings with 1 sec to 99 hour intervals
- Special software for 21 CFR Part 11 compliance
- BioCote® antimicrobial protection
- Waterproof and rugged IP67 case

EVt Range

EVt2 Transport logger, multi-use

EVSW Software, standard

EVSWPRO Software for use with 21CFR Part 11

EVTCRUSB PC interface for programming and downloading data with USB connector