



### RF311-T Temperature Data Logger

Measures temperature in the environment in which it is situated.

- Measures the temperature of the environment in which it is situated.
- Temperature range:  $-4$  to  $+140^{\circ}\text{F}$
- Supplied with wall bracket and micro USB lead



### RF312 Glycol Temperature Data Logger

Designed to monitor the temperature of perishable goods using a detachable Glycol buffer probe.

- Temperature measurement range:  $-40$  to  $+257^{\circ}\text{F}$
- Supplied with high accuracy glycol buffer probe, wall bracket and micro USB lead



### RF314 Dual Temperature Data Logger with two Thermocouple Probes

Measures two temperature points with one device via two thermocouple probes.

- Temperature range:  $-454^{\circ}\text{F}$  to  $+2372^{\circ}\text{F}$
- Sub-miniature connection is compatible with a range of Comark probes
- Supplied with removable thermocouple probe, wall bracket and micro USB Lead



### RF312-TP Temperature Data Logger with Thermistor Probe

Measures temperature via a thermistor probe.

- Measures temperature using a thermistor probe.
- Temperature range:  $-40^{\circ}\text{F}$  to  $+257^{\circ}\text{F}$
- Supplied with one removable thermistor probe, wall bracket and micro USB lead



### RF313-TH Temperature and Humidity Data Logger

Measures temperature and humidity levels in the environment in which it is situated.

- Temperature range:  $-4^{\circ}\text{F}$  to  $+140^{\circ}\text{F}$
- Humidity Range:  $0\%RH$  to  $100\%RH$
- Supplied with wall bracket and micro USB lead



### RF312 Dual Plus Temperature Data Logger with two Thermistor Probes

Measures two temperature points with one device via two thermistor probes.

- Temperature measurement range:  $-40^{\circ}\text{F}$  to  $+257^{\circ}\text{F}$
- Supplied with two removable thermistor probes, wall bracket and micro USB lead



### RF314-TC Temperature Data Logger with Thermocouple Probe

Measures temperature via a thermistor probe.

- Temperature range:  $-454^{\circ}\text{F}$  to  $+2372^{\circ}\text{F}$
- Sub-miniature connection is compatible with a range of Comark probes
- Supplied with one removable thermocouple probe, wall bracket and micro USB lead



### RF324 Alarm Unit

Connects to multiple Diligence WiFi data loggers via WiFi network

- Flashing red LED's light up through translucent red rear moulding
- Configurable alert tones and volume