



We put space to work.

Item # \_\_\_\_\_

Job \_\_\_\_\_

# Metro® Mightylite™ Insulated Food Carrier Accessories

## Dolly (MLD1)

Heavy-duty high density polyethylene (HDPE) construction fastened to 0.100" (2.5mm) thick aluminum caster channels with rugged 5/16" (8mm) stainless steel tie down anchors. Plate mounted casters, 2 swivel and 2 swivel with brakes. 5" (127mm) diameter donut neoprene wheels. Load capacity 350 lbs. (158kg) per dolly. Includes 1" (25mm) x 15' (457 cm) long cam buckle strap with hooks. Dolly is designed to transport carriers or milk crates. Stores on top of carrier to save space.



Cat. No.	Description	Dimensions (W x D x H)		Product Weight	Shipping Weight	Shipping Volume
		(in)	(mm)			
<b>MLD1</b>	Dolly for ML300, 400, 180, 180XL (Includes Strap)	20.7 x 29.8 x 9.5	524 x 756 x 241	19.0 lbs. (8.6 kg)	20.0 lbs. (9.1 kg)	3.5 ft³ (0.99m³)

## Thermal Partition (MLP1)

1.5" (38mm) thick insulated partition helps avoid accelerated food temperature loss or gain inside partially full carriers by minimizing empty space inside the carrier. Also use to separate hot and cold food in one carrier. Lightweight, insulated, durable expanded polypropylene (EFF) construction.



Cat. No.	Description	Dimensions (W x D x H)		Product Weight	Shipping Weight	Shipping Volume
		(in)	(mm)			
<b>MLP1</b>	Thermal Partition for ML300, 400, 180, 180XL	13 x 21 x 1.5	330 x 533 x 38	0.8 lbs. (0.4 kg)	1.5 lbs. (0.7 kg)	0.3 ft³ (0.01m³)

## Wire Caddy (MLC1)

Can be used to hold hot and cold packs to extend holding times, as a support for disposable aluminum pans, or to organize and transport common items such as quart containers. Epoxy coated. One included with every front-load carrier.



Cat. No.	Description	Dimensions (W x D x H)		Product Weight	Shipping Weight	Shipping Volume
		(in)	(mm)			
<b>MLC1</b>	Wire Caddy for ML300, 400	13 x 21 x 1	330 x 533 x 25	1.3 lbs. (0.6 kg)	2 lbs. (0.9 kg)	0.3 ft³ (0.01m³)

All Metro Catalog Sheets are available on our website: [www.metro.com](http://www.metro.com)



**InterMetro Industries Corporation**  
North Washington Street, Wilkes-Barre, PA 18705  
Product Information. U.S. and Canada: 1.800.992.1776  
Outside U.S. and Canada: [www.metro.com/contactus](http://www.metro.com/contactus)

L02-221  
Printed in U.S.A. 1/19

Information and specifications are subject to change without notice. Please confirm at time of order.

Copyright © 2019 InterMetro Industries Corp.



**Metro®** Mightylite™ Insulated Food Carrier Accessories

**13-62**

Job \_\_\_\_\_



We put space to work.®

# Metro® Mightylite™ Insulated Food Carrier Accessories

## Heater (MLH1, MLHX1)


Stainless steel, add-on carrier heater with polymer handles and rubber feet. Great for applications where carriers are frequently accessed or not 100% full, or simply when added heat is desired to keep food hotter, safer, and more appetizing. Thermostatically controlled, reaches max temperature in approximately 10 minutes. Approximate top-center surface temperature range from 150°F (66°C) to 200°F (94°C). 72" long, permanently attached power cord with cord wrap. Power indicator lights up when plugged in.



Cat. No.	Description	Electrical Specifications	Dimensions (W x D x H)		Shipping Weight	Shipping Volume
			(in)	(mm)		
<b>MLH1</b>	120V Heater for ML300, 400, 180, 180XL	120V, 200W, NEMA 5-15P	20.6 x 12.4 x 1.6	524 x 315 x 40	9.2 lbs (4.2 kg)	0.3 ft³ (0.01 m³)
<b>MLHX1</b>	240V Heater for ML300, 400, 180, 180XL	240V, 200W, NEMA 6-15P	20.6 x 12.4 x 1.6	524 x 315 x 40	9.2 lbs (4.2 kg)	0.3 ft³ (0.01 m³)

## Serving Ring (MLW1)

For use with top-load carriers and heater to transport & serve with a single solution that does not require water or canned fuel. Wire serving ring can also be used without carrier with chaffing pan and canned fuel. Accommodates full & fractional sized pans, and non-pan items such as individually portioned meals. Epoxy coated wire construction.



Cat. No.	Description	Dimensions (W x D x H)		Product Weight	Shipping Weight	Shipping Volume
		(in)	(mm)			
<b>MLW1</b>	Serving Ring ML180, 180XL	21.7 x 12.8 x 7.8	551 x 325 x 199	3.7 lbs (1.7 kg)	4.7 lbs (2.1 kg)	1.4 ft³ (0.04 m³)

## Carrying Strap (MLS1)

Heavy-duty adjustable strap, designed to work with top-load and front-load carriers. Detachable handles can be quickly re-configured for one-handed or two-person carrying. 1" (25mm) wide, high-strength polyester webbing with low water absorption properties. Box sewn stitch pattern with durable polymer / metal hardware



Cat. No.	Description	Shipping Weight	Shipping Volume

an Ali Group Company



The Spirit of Excellence