

## STANDARD REMOTE AIR-COOLED CONDENSER

Model	For use with Remote Ice Machine	Electrical	Shipping Weight	Replaces Model
JCF0500-161	iF0500N	115v/60hz/1	64 lbs / 29 kg	JC0495-161
JCF0500-161Q	iF0500N	115v/60hz/1	65 lbs / 29 kg	JC0495-161Q
JCF0900-261	iF0600N & iF900N	208-230v/60hz/1	78 lbs / 35 kg	JC 0895 and 0995-261
JCF0900-261Q	iF0600N & iF900N	208-230v/60hz/1	79 lbs / 36 kg	JC0995-261Q
JCT1200-261	iT1200N	208-230v/60hz/1	78 lbs / 35 kg	JC0995-261
JCT1500-261	iT1500N and iT1900N	208-230v/60hz/1	80 lbs / 36 kg	JC1395-261
JCT1500-261Q	iT1500N and iT1900N	208-230v/60hz/1	81 lbs / 37 kg	JC1395-261Q
JCF0900-251	iF0600N and iF0900N	230v/50hz/1	78 lbs / 35 kg	JC0895 and 0995-251
JCT1200-251	iT1200N	230v/50hz/1	78 lbs / 35 kg	JC0995-251
JCT1500-251	iT1500N and iT1900N	230v/50hz/1	80 lbs / 36 kg	JC1395-251

NOTE: Models with Q suffix are available with coated coils that provide extra corrosion protection in salt spray environments Coated Coil models require longer lead time, please contact the factory.



K00129

## STANDARD REMOTE TUBING KITS & ACCESSORIES Shipping Weight Tubing For use with Series Length RT20R404 iF0500, iF600 and iF900 Precharged with quick connects 20ft / 6.1m 10 lbs / 5 kg RT35R404 iF0500, iF600 and iF900 Precharged with quick connects 35 ft / 10.7m 15 lbs / 7 kg iF0500, iF600 and iF900 Precharged with quick connects 22 lbs / 10 kg RT50R404 50 ft / 15.2m RT20R410A iT500 and iT1200 Precharged with quick connects 20 ft / 6.1 m 10 lbs / 5 kg RT35R410A iT500 and iT1200 Precharged with quick connects 35 ft / 10.7m 15 lbs / 7 kg RT50R410A iT500 and iT1200 Precharged with quick connects 50 ft / 15.2m 22 lbs / 10 kg **RL20R410A** iT1500 and iT1900 Precharged with quick connects 20 ft / 6.1 m 10 lbs / 5 kg iT1500 and iT1900 Precharged with quick connects RL35R410A 35 ft / 10.7m 15 lbs / 7 kg **RL50R410A** iT1500 and iT1900 Precharged with quick connects 50 ft / 15.2m 22 lbs / 10 kg **ACCESSORY**

NOTE: Manitowoc remote systems are only approved and warranted as a complete new package. Replacing an ice machine with an S or Indigo remote model requires a <u>NEW</u> condenser and line set. Use of a new multi-circuited condenser is approved when sized and installed as outlined in Manitowoc Product Information. Rack system applications are not approved.

2 lbs / 1 kg

Remote Coupling Kit needed for non-Manitowoc Tubing

TOP AIR DISCHARGE KIT					
Kit	For use with Series	Shipping Weight			
K00379	Indigo NXT iT0450, iT0500, iF0600, iT0750	18 lbs / 9 kg			
K00438	Indigo NXT iT0420 and iT0620 models	17 lbs / 8 kg			
K00439	Indigo NXT iF0900	17 lbs / 8 kg			
K00449	Indigo NXT iT1200	18 lbs / 9 kg			
K00481B	Indigo NXT iT1500 and iT1900 models	29 lbs/ 13 kg			

NOTE: Top air discharge kits are used when there is not sufficient clearance on the sides of an air cooled machine. These kits change the side panels and top panel so the air intake is from the back of the machine and the exhaust is re-routed out of the top of the machine rather than the sides.