ICB Twin, 120/240V SST

Height: 26.9" Width: 20.2" Depth: 24.7" (68.3cm) (51.3cm) (62.7cm)





- Sleek modernized design language, with rounded angles on the corners and trunk
- Brews into 2.5 to 3.8L (84 to 128 oz)airpots and 3.8 to 5.7L (1 to 1.5 gallon) baseless Thermofresh servers
- Digital readout displays in English, Spanish, or French ---for easier programming and control--- and can show either 'Standard' or Metric measurements. Digital readout also shows machine status, and targeted advertising messages can be programmed for display.
- Large 5.6 gallon (21.2L) tank provides back-to-back brewing capacity
- BUNN Infusion Series technology allows for multiple recipes from one footprint --with three brew buttons and two batch sizes
- Energy-saver mode reduces tank temperature during idle periods
- Exclusive Peak Extraction™ Sprayhead is multi-directional with a 17-hole design to ensure ultimate uniformity of extraction
- Electronic funnel lock prevents removal of each brew funnel until drip- through is complete
- USB programming capable
- · Brew counter keeps track of how many batches are brewed
- Pre-infusion and pulse brew for maximum flavor extraction. Cold brew lockout & digital temperature control further ensure top-notch brewing.

Additional Features

• Hot water faucet (supplied for custom installation)

A Servers not included unless otherwise noted





Specifications

Product #: 53200.0100 Funnel: Black Plastic

Water Access: Plumbed Interface: Wireless Finish: Stainless

Electrical & Capacity

Volts*	Amps	Watts	Cord Attached	Plug Type	8oz cups/hr 236ml cups/hr	Input H ² O Temp.	Phase	# Wires plus Ground	Hertz
120/240	25	6000	Yes/	-	280	60°F (15.5°C)	1	3	60

"When a BUNN is machine rated 120/208-240V, 120/208V or 120/240V, the higher voltage is the supply voltage needed to power the machine. The 120V is there to supply power to some components rated 120V in the machine, but it is not the supply voltage and would not power the machine if the machine is marked with the before mentioned ratings.

Plumbing Requirements


	<u> </u>				
PSI	kPa	Fitting Supplied	Water Flow Required (GPM)		
20-90	138-621	3/8" Male Flare Fitting	1.00		

CAD Drawings

2D	Revit	KLC		
•	•	•		

MARNING:





Unit				Shipping				
	Height	Width	Depth	Height	Width	Depth	Weight	Volume
English	26.9 in.	20.2 in.	24.7 in.	30.0 in.	23.9 in.	28.4 in.	78.460 lbs	11.761 ft³
Metric	68.3 cm	51.3 cm	62.7 cm	76.2 cm	60.6 cm	72.1 cm	35.589 kgs	0.333 m³



Related Products & Accessories: ICB Twin, 120/240V SST(53200.0100)



FILTERS, GOURMET 500 500/1 50/CL

Product #: 20138.1000





Serving & Holding Options: ICB Twin, 120/240V SST(53200.0100)



AIRPOT, 2.5L GL PB SINGLE PK

Product #:13041.0001



AIRPOT, 2.5L GL PB 6/ CASE

Product #:13041.0101



AIRPOT, 2.5L SST LA SINGLE PK

Product #:32125.0000



AIRPOT, 2.5L SST LA 6/ CASE

Product #:32125.0100



AIRPOT, 3.0L SST LA SINGLE PK

Product #:32130.0000



AIRPOT, 3.0L SST LA 6/ CASE

Product #:32130.0100



AIRPOT, 3.8L SST LA SINGLE PK

Product #:36725.0000



AIRPOT, 3.8L SST LA 6/ CASE

Product #:36725.0100



STAND ASSY, TF SERVER

Product #:39795.0003



TF SERVER, DSG2 1G SST NOBASE

Product #:42700.0050



TF SERVER, DSG2 1G BLK NOBASE

Product #:42700.0051



TF SERVER, 1G DSG GEN3 NOBASE

Product #:42700.0250



TF SERVER,DSG2 1.5G SST NOBAS

Product #:42750.0050



TF SERVER, 1G/3.8L MECH NOBASE

Product #:44000.0050



TF SERVER, 1G/3.8L MECH BLK NOBASE

Product #:44000.0051



TF SERVER, 1G MECH GEN3 NOBASE

Product #:44000.0250



TF SERVER, 1.5G/5.7L MECH NOBASE

Product #:44050.0050



TF SERVER, 1.5G/5.7L MECH BLK NOBASE

Product #:44050.0051



STAND ASSY, TF SERVER

Product #:54473.0000



STAND ASSY KIT, TF SERVER

Product #:54473.1000