HEATED TRANSPORT CARTS

FOR 12"x20" STEAM TABLE PANS

Features & Benefits

- Models available with top or bottom mounted forced air heating
- Models with channel, angle or universal slides for a variety of pan sizes
- Under-counter, 1/2 height, 3/4 height and full height cabinets
- All heating systems feature convection air heating for fast heat-up and recovery as well as even heating
- All stainless steel, welded unibody construction for durable long life
- Non-marking floating style wrap-around bumper is standard (except PH125, PH128 & PH129). Absorbs shocks and minimizes damage to cart and facility walls.
- Offset wheel-ahead caster configuration for a smoother ride over uneven surfaces (except PH125, PH128 & PH129)
- Optional full perimeter wrap-around bumper (PH125, PH128 & PH129)



Heated Transport Carts with Channel Slides for 12"x20" Pans - Top-Mount Heat



Model Number	Pan Capacity* 12"x20"x2.5"	Inside Working Height in (mm)	Ove Height	rall Dimensio Depth in (mm)	ns Width	Caster Diameter in (mm)	Class 100 Shipping Wt. Ibs (kg)
PH125 (under-counter)	5	20-1/2 (521)	28-1/2 (724)	25-1/8 (638)	17-7/8 (454)	3 (76)	110 (50)
PH128	8	23-5/8 (600)	37-3/4 (946)	25-1/8 (638)	17-7/8 (454)	4 (102)	128 (58)
PH129	9	26 (660)	40-1/2 (1029)	25-1/8 (638)	17-7/8 (454)	4 (102)	134 (61)

^{*}Spacing is fixed on 2-3/4"centers

Heated Transport Carts with Channel Slides for 12"x20" Pans - Bottom-Mount Heat



Model Number	Pan Capacity* 12" x 20"x2.5"	No. of Doors	Inside Working Height in (mm)	Over Height	rall Dimensio Depth in (mm)	ns Width	Caster Diameter in (mm)	Class 100 Shipping Weight
PH1200	16	1	46 (1168)	58 (1473)	28 (711)	24 (610)	5 (127)	280 (127)
PH1215	21	2	30 (762)	42 (1067)	28 (711)	46-3/4 (1187)	5 (127)	325 (147)
PH1225	33	2	46 (1168)	58 (1473)	28 (711)	46-3/4 (1187)	5 (127)	350 (159)
PH1250	50	3	46 (1168)	58 (1473)	28 (711)	65-1/4 (1658)	5 (127)	450 (204)

^{*}Channel slides with spacing fixed on 2-3/4" centers. Specify pan/tray size when ordering.

PH1200

PH1215
PH1225
PH1250

See page 75 for Options and Accessories



Electrical Information

PH125 PH128 PH129 Electrical Information NEMA Plug Type

1530 watts 120 volts 12.8 Amps 60 Hz Single Phase Electrical Information
NEMA Plug Type

1650 watts
120 volts
13.7 Amps
60 Hz
Single Phase

PH1215 PH1225 PH1250



72

