



Job: Item No.:

Notes:

Model Number: PH185 PH181 PH1810
 PH1830 PH1860

Heated Transport Carts

SPECIFICATIONS



PH1830

DESCRIPTION

PH Series Heated Food Transport Cabinets are designed to hold and transport cooked food warm and ready for serving. They are constructed of sanitary stainless steel and feature a bottom-mounted lift-out heating system with dial controls and blower heat for even air flow throughout the cabinet. Transport features include wrap-around bumper, wheel-ahead caster pattern and insulated turned-in seam construction.

SHORT FORM SPECIFICATIONS

Heated food transport cart, electric, insulated, welded, turned-in seam stainless steel construction with side-mounted push handles and flush-mounted transport latch with finger grip. Lift-out, convection heater. Stainless steel tray racks with universal adjustable tray slides on 1.75" centers. Standard 3.5" spacing for 18"x26" sheet pans and 12"x20" steam table pans. Non-marking gray vinyl wrap-around bumper. Polyurethane casters set in wheel-ahead caster pattern. 120V, 60Hz, 1Ph, 1650 watts, 13.7A, ten-foot 3 wire rubber cord with 3-prong grounding plug. NEMA 5-15P.

FEATURES

- Bottom mounted, removable convection heating system
- Dial thermometer with remote sensing bulb
- Capable of heating to 200°F (93°C); pre-heat to 160°F (71°C) in approximately 25 minutes
- All welded, turned-in seam, stainless steel construction
- 14 ga. stainless steel caster bolsters; 1"x1"x14 ga. perimeter tube supports welded to bolsters
- Two heavy-duty aluminum vertical push handles bolted to sides with reinforced back-up plates
- Double panel door with vinyl gasket; 1.5" thick high-density fiberglass insulation
- Concealed, stainless steel pin hinge; 270° door swing
- Sliding latch with finger grip
- High temperature magnetic door gasket
- All-swivel polyurethane casters; two fitted with brakes
- Offset wheel-ahead caster pattern
- Non-marking gray vinyl bumper set in heavy-duty extruded aluminum frame
- Removable racks with adjustable tray slides
- Accommodates 18"x26" sheet pans, 12"x20" steam table pans, GN 1/1 and GN 2/1 pans and 20"x20" glass racks

OPTIONS AND ACCESSORIES

- Menu card holder
- Polycarbonate thermometer cover
- Top mounted transport latch with padlock hasp
- Side-mounted transport latch (n/a on PH1860)
- Locking paddle-style door latch
- Rack hold down device
- Heater hold down device
- Tamper-resistant fasteners
- Stainless steel push handles
- Alternate electrical configuration
- Alternate caster sizes and types
- Removable canned fuel holder
- Stainless steel door gasket
- Wire shelves
- Close-fit bumper
- Marine package
- Correctional package

CERTIFICATIONS



WARRANTY

One-year warranty for parts and labor.



CARTER-HOFFMANN
1551 McCormick Avenue, Mundelein, IL 60060
847.362.5500 • 800.323.9793
www.carter-hoffmann.com

Follow us



Form PH18U Series
_0821







Job: Item No.:

Notes:

Model Number: PH185 PH181 PH1810
 PH1830 PH1860

Heated Transport Carts

SPECIFICATIONS



CLEARANCES

A clearance of at least 2” from any wall or combustible material. A clearance of least 36” at the front of the cabinet is required to open the door. Cabinet must be placed on a solid level floor.

ELECTRICAL DATA

Single electrical connection.
 120 Volts, 1650 Watts, 13.7 Amps, 60Hz, single phase.
 Ten foot three wire rubber cord with 3-prong grounding plug. NEMA 5-15P.



Model Number	Pan Capacity*		Inside Working Height		Height [A]		Depth [B]		Width [C]		Caster Diameter		Shipping weight	
	18"x26"	12"x20"	in	mm	in	mm	in	mm	in	mm	in	mm	lbs	kg
PH185	5	10	20 ^{7/8}	349	30 ^{1/2}	775	36	914	30 ^{5/8}	730	3	76	225	102
PH181	6	12	23 ^{1/5}	597	36 ^{1/8}	918	36	914	30 ^{5/8}	730	5	127	240	109
PH1810	13	26	46	1168	59 ^{1/4}	1473	36	914	30 ^{5/8}	730	5	127	385	175
PH1830	16	32	57 ^{1/4}	1454	71	1803	36	914	30 ^{5/8}	730	6	152	425	193
PH1860	26	52	46	1168	59 ^{1/4}	1473	36	914	55 ^{7/8}	1419	6	152	568	258

*Pan spacing at 3.5” (89mm). Tray slides adjustable at 1.75” increments.

Due to periodic changes in designs, methods, procedures, policies and regulations, the specifications contained in this sheet are subject to change without notice. While Carter-Hoffmann exercises good faith efforts to provide information that is accurate, we are not responsible for errors or omissions in information provided or conclusions reached as a result of using these specifications. By using the information provided, the user assumes all risks in connection with such use.