



DIGITAL

- ◆ Easy-read LCD display
- ◆ Excellent, quick response times for fast temperature readings

| ITEM | NSF | TEMPERATURE RANGE | LCD | PROBE | GUIDELINE ON DIAL | MOUNTING / OTHER FEATURES | UOM | CASE |
|---------|-----|-------------------------------|--------------------|---------|-----------------------------------|--|------|--------|
| TMT-DG1 | | -40° - 302°F; -40° - 150°C | 1" | 4-3/4"L | Meat Cooking Temperature Guide | | Each | 12/144 |
| TMT-DG2 | N/A | -49° - 392°F; -45° - 200°C | 1-3/16" | 4-3/4"L | Meat Cooking Temperature Guide | • Easy-Read LCD Swivels 180° | Each | 12/72 |
| TMT-DG4 | | -40° - 450°F; -40° - 230°C | 1-1/4" | 3-1/8"L | HACCP | • Hold Function | Each | 3/144 |
| TMT-DG5 | N/A | -49° - 392°F; -45° - 200°C | 1-3/8" Back-Lit | 2-7/8"L | Meat Cooking Temperature Guide | • Min. & Max. Feature • Hold Function • Lanyard | Each | 12/72 |
| TMT-DG6 | N/A | -58 - 572°F; -50 - 300°C | 1-7/8" | 6"L | | • Flip-Down Stand • Magnet Included | Set | 24/96 |
| TMT-DG7 | | -40° - 572°F; -40° - 300°C | 1-1/2" | 4"L | | • 1.5mm Step-Down Folding Probe • Hold & Auto-Off Functions • Field recalibratable | Each | 12/72 |

WATERPROOF DIGITAL THERMOMETERS

- ◆ Compact thermometers provide fast temperature readings for liquids or solids
- ◆ Easy-read LCD display

| ITEM | NSF | TEMPERATURE RANGE | LCD | PROBE | MOUNTING / OTHER FEATURES | UOM | CASE |
|---------|-----|-------------------------------|---------|---------|--|------|-------|
| TMT-WD1 | | -58° - 392°F; -50° - 200°C | 7/8" | 2-3/4"L | • Hold Function • Protective Sleeve | Each | 24/96 |
| TMT-WD2 | | -40° - 450°F; -40° - 232°C | 1-3/8"W | 2-3/4"L | • 1.5mm Step-Down Folding Probe • Auto-Off Function • Lanyard Included | Each | 12/96 |
| TMT-WD3 | | -40° - 500°F; -40° - 260°C | 1"W | 5"L | • 1.5mm Step-Down Folding Probe • Min./Max. and Hold Functions • Antimicrobial Protective Sleeve • Field recalibratable | Each | 24/72 |

INFRARED THERMOMETER

- ◆ Point at surface to get an accurate temperature reading, with no risk of cross-contamination.
- ◆ Automatically turns off after idle for 20 seconds
- ◆ Distance to spot ratio 12:1

| ITEM | NSF | TEMPERATURE RANGE | LCD | MOUNTING / OTHER FEATURES | UOM | CASE |
|---------|-----|-------------------------------|----------------|-------------------------------------|------|-------|
| TMT-IF1 | N/A | -26° - 608°F; -32° - 320°C | 1" Back-Lit | • Auto temp. hold • Laser ON/OFF | Each | 12/48 |

