

MOBILE TRAY AND GLASS RACK DISPENSERS | STAINLESS STEEL

Mobile dispensers allow quick transporting and refilling so your customers can readily access trays.

- Adjusting height level is easy and convenient. Simply detach and attach springs as needed with no tools required

- Handy platform base stores empty trays or racks for added storage
- All 4" swivel casters, 2 with brake, allow easy maneuverability.
- Stainless steel construction ensures long life and durability
- Stainless steel material is easy to clean and sanitize, stain- and rust-resistant
- Perimeter bumper protects walls and furnishings



Model 986 includes convenient flatware dispenser to accommodate eight flatware cylinders (cylinders not included)

ACCESSORIES:

- Flatware cylinder rack (for Model 999)



Simply detach or attach springs to adjust tension for the height level you desire.



Model #997



Model #996

Freight Class: **92.5**
Ships in: **3** days or less!



Model	Capacity	Accommodates Tray/Rack Size	Overall Size			Case Weight Lbs. (Kg)	Case Cube Cu. ft. (m ³)
			W	L	H		
986* Open 2 sides	150 ea. 150 ea.	14" x 18" (356 x 457) Trays 15" x 20" (381 x 508) Trays	23-3/4" (603)	19-7/8" 505	50-7/8" 1292)	92 (41.7)	15.8 (.61)
996 Open 2 sides	150 ea. 150 ea.	14" x 18" (356 x 457) Trays 15" x 20" (381 x 508) Trays	23-3/4" (603)	19-7/8" 505	36-1/8" 918)	80 (36.3)	15.8 (.61)
997 Open 2 sides	14 ea. 7 ea.	10" x 20" (254 x 508) Racks* 20" x 20" (508 x 508) Racks*	25-11/16" (652)	23-3/4" 603	36-1/8" 918)	82 (37.2)	18.4 (.71)
998 Enclosed sides	14 ea. 7 ea.	10" x 20" (254 x 508) Racks* 20" x 20" (508 x 508) Racks*	25-11/16" (652)	23-3/4" 603	36-1/8" 918)	94 (42.6)	18.4 (.71)
999 Enclosed sides	150 ea. 150 ea.	14" x 18" (356 x 457) Trays 15" x 20" (381 x 508) Trays	23-3/4" (603)	19-7/8" 505	36-1/8" 918)	88 (39.9)	15.8 (.61)

Measurements in () denote metric millimeters, unless otherwise specified. *Rack capacity based on 4" (102) high rack. *Model 986 includes flatware dispenser (cylinders not included).
Lake-Glide® Casters: 4" (102) - All swivel, extra load, 2 w/brakes.