

SANDWICH/SALAD UNITS - CLEAR LID NATURAL Refrigerant

■ **Digital temperature control & monitor system**

Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

■ **Hydrocarbon refrigerants (R-600a)**

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

■ **Cold Bunker system**

Our innovative forced air system allows cold air to flow all around the food pan area, covering not only underneath the pan, but also the front, top and the rear. This unique air flow creates a cold air-shield around the pan, which maintains the food temperature at under 41°F (NSF requirement) even when the lids are opened. In addition, the compartment isolates pans from the reach-in area to prevent food spillage.

■ **Stainless steel exterior**

The Turbo Air M3 model boasts a stainless steel exterior (galvanized steel back and bottom). Interior is AL cabinet with stainless steel floor and ABS door liner. It guarantees the utmost in cleanliness and long product life. The M3 model adds a touch of style to the most refined setting.

■ **High-density polyurethane insulation**

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

■ **Ergonomically designed doors**


Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience. ABS sheet door liners resist water condensation with thermal efficiency.

■ **9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail**

■ **Adjustable, heavy duty, PE (polyethylene) coated wire shelves**

■ **Front Breathing airflow**

Front Breathing airflow is designed to draw in air and discharge from the front, allowing units to run at high efficiency in tight spaces and eliminates the need for surrounding clearances.



LED interior lighting & fan control (only at Turbo Air)

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

■ **Refrigerator holds 33°F ~ 39°F for the best in food preservation**

■ **Standard features**

- Anti-corrosion coated evaporator
- Self-contained system
- 3" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included
- High-density polyurethane insulation
- Lead time applies (8~10 weeks)

■ **Optional features**

- Legs available for all models: 6"
- Door locks available (extra lead time will apply)
- Casters available for all models: 2.5", 5"

MST MODELS SPECIFICATIONS

ELECTRICAL DATA		MST-24S-N6
Voltage		115/60/1
Plug Type		NEMA 5-15P
Full Load Amp.		2.6
Compressor HP		1/5
Cord Length (ft.)		9
Refrigerant		R-600a
DIMENSIONAL DATA		
Net Capacity (cu. ft.)		2.83
Ext. Dimension (L x D [*] x H [†]) (in.)		24 x 23 ⁵ / ₈ x 28 ¹ / ₈
# of Doors		1
# of Shelves (Size (L x D) (in.))		1 (19 ³ / ₈ x 11 ¹ / ₈)
# of Pan		6
Net Weight (lbs.)		126
Gross Weight (lbs.)		137

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1" for rear spacers. Depth does not include 3-3/8" for cutting board. † Height does not include 3-7/8" for caster height.

■ **WARRANTY: 3 Year Parts and Labor Warranty, Additional 2 Year Warranty on Compressor**