EUROPEAN STRAIGHT DISPLAY CASES NATURAL

Self-Cleaning Condenser Equipped Units

■ Self-Cleaning Condenser (Patented)

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Attractive, elegant, glass sided Euro design Straight tempered front glass and minimal frame provide full product visibility to optimize display effects. Its elegant contemporary euro design and luxurious colored case will not only enhance any store atmosphere but also will keep product presentation at its best and most beautiful.

High-density polyurethane insulation The entire cabinet structure is foamed-in-place using high density, CFC free polyurethane insulation.

- Low-E coated double pane glass is tempered for safety
- Adjustable, tempered glass shelves with stainless steel front and back edges
- Stainless steel floor and airflow grille
- Sliding rear doors for product loading & unloading
- Rear access to compressor compartment for quick and easy service
- Stainless steel color option available



Maintenance free, Self-Cleaning Condenser

TCGB-72UF-W-N

■ Refrigerated bakery case holds avg. 33°F ~ 41°F for fresher bakery products

Standard features

- No plumbing required
- · White and black colors come standard
- Safety shielded LED interior lighting
- · Solar powered digital thermometer
- Digital electronic thermostat with defrost control

- Recommended operating conditions

TCGB models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively.

TCGB MODELS SPECIFICATIONS

ELECTRICAL/DIMENSIONAL DATA	TCGB-36UF-W(B, S)-N	TCGB-48UF-W(B, S)-N	TCGB-60UF-W(B, S)-N
Voltage	115/60/1	115/60/1	115/60/1
Plug Type			
Full Load Amp.	7.5	7.5	8.6
Compressor HP	1/3	1/3	3/4
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	11.8	15.6	19.4
Ext. Dimension (L x D x H*) (in.)	361/2 x 331/8 x 501/8	481/2 x 331/8 x 501/8	601/2 x 331/8 x 501/8
# of Shelves	2	2	2
Shelf Size (L x D) (in.)	323/8 x 163/4, 323/8 x 183/4	443/8 x 163/4, 443/8 x 183/4	563/8 x 163/4, 563/8 x 183/4
Net / Gross Weight (lbs.)	439 / 551	540 / 666	637 / 776

ELECTRICAL/DIMENSIONAL DATA	TCGB-72UF-W(B, S)-N	TCGB-60UF-CO-W(B, S)-N	TCGB-72UF-CO-W(B, S)-N
Voltage	115/60/1	115/60/1	115/60/1
Plug Type			
Full Load Amp.	8.6	7.5	7.5
Compressor HP	3/4	1/3	1/3
Refrigerant	R-290	R-290	R-290
Net Capacity (cu. ft.)	23.2	10.3 x 2	12.2 x 2
Ext. Dimension (L x D x H*) (in.)	721/2 x 331/8 x 501/8	601/2 x 331/8 x 501/8	721/2 x 331/8 x 501/8
# of Shelves	2	4	4
Shelf Size (L x D) (in.)	683/8 x 163/4, 683/8 x 183/4	(2) 271/4 x 163/4, (2) 271/4 x 183/4	(2) 331/4 x 163/4, (2) 331/4 x 183/4
Net / Gross Weight (lbs.)	831 / 992	705 / 844	899 / 1,060

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

^{*} Height does not include 5/8" for bolt height.

[■] WARRANTY: 2 Year Parts and Labor Warranty, Additional 3 Year Warranty on Compressor