

VERTICAL OPEN DISPLAY CASES NATURAL Refrigerant

Self-Cleaning Condenser Equipped Units

Self-Cleaning Condenser (Patented)

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Modern design

By integrating great contours with durable structures, our modern style product designs are user-friendly while maintaining the highest product visibility and aesthetics. Safety reinforced tempered glass front shield and side walls optimize the merchandiser's display effects of fresh salads, sandwiches, desserts and beverages. Its elegant contemporary euro design will enhance any store application.

Designed to enhance impulsive sales

Ideal for eye-catching displays and convenient access with fast service in high traffic area.

Tempered glass shelves standard (Cantilever type)

Standard back-guard improves airflow

Foamed with polyurethane, high-density cell insulation (CFC free)

Perforated interior back wall and top for improved airflow

Front air intake and rear air discharge

Digital temperature controller

Stainless steel color option available

Standard features

- Simple plug-in installation
- No plumbing required
- White and black colors come standard
- Digital electronic thermostat with defrost control
- LED interior lighting
- 2.5" dia. swivel casters with lock on the front set
- Lead time applies



Maintenance free, Self-Cleaning Condenser

TOM20-60N-W



TOM20-75N-B

Optional features

- Price tag channel available

Recommended operating conditions

TOM models are designed to operate in an environment where temperature & humidity do not exceed 75°F and 55% respectively. Units should not be installed near HVAC vents, fans or doorways that will disrupt the air curtain and compromise the function of the cabinet. Air curtain models will run most efficiently when completely loaded with product.

TOM MODELS SPECIFICATIONS

ELECTRICAL DATA	TOM20-60N-W(B, S)	TOM20-75N-W(B, S)
Voltage	115/60/1	115/60/1
Plug Type	Ⓢ NEMA 5-20P	Ⓢ NEMA 5-20P
Full Load Amp.	11.2	12.2
Compressor HP	3/4	3/4
Refrigerant	R-290	R-290
DIMENSIONAL DATA		
Net Capacity (cu. ft.)	3.2	4.8
Ext. Dimension (L x D x H†) (in.)	19 ⁵ / ₈ x 25 ⁵ / ₈ x 56 ³ / ₄	19 ⁵ / ₈ x 25 ⁵ / ₈ x 72 ¹ / ₂
# of Shelves	2	4
Shelf Size (L x D) (in.)	18 x 9 (1), 18 x 11 (1)	18 x 9 (1), 18 x 11 (3)
Net Weight (lbs.)	285	350
Gross Weight (lbs.)	330	400

Design and specifications subject to change without notice. Most updated spec sheets are available at www.turboairinc.com.

Actual shipping weight may differ due to extra packing materials for product protection.

* Depth does not include 1" for rear spacers. † Height does not include 2-3/4" for caster height.

WARRANTY: 2 Year Parts and Labor Warranty, Additional 3 Year Warranty on Compressor