

Conserver[®] XL-E

Project _____
 Item _____
 Quantity _____
 CSI Section 11400
 Approval _____
 Date _____

Conserver[®] XL-E

Models

Conserver[®] XL-E



Standard Features

- Electronic timer
- Internal sump design
- Built-in waste accumulator
- Delimer switch for easy removal of hard water deposits
- Removable scrap screen
- Air gap instead of vacuum breaker
- Door switch
- Convenient top mounted controls
- Auto start
- Interchangeable upper and lower stainless steel wash/rinse arms
- Wash thermometer
- Low chemical indicator lights
- Stainless steel adjustable bullet feet

Mandatory Specs

Specify voltage _____

Options

- Water Hammer Arrestor
- Scaltrol
- False Panel (for corner installations)
- Front Dress Panel
- Flanged Feet
- Audible Low Product Alarm
(available only on 115v models)

Accessories

- 36-Compartment Rack
 - 4-1/8" tall (105 mm)
 - 5-5/8" tall (143 mm)
 - 7" tall (178 mm)
- Combination Rack
- Peg Rack

Specifications

- Uses 1.02 gallons (3.86 liters) water per rack
- 41 (39)* racks per hour (Normal cycle)
- Single point electrical connection
- Self-draining stainless steel pump eliminates soil/detergent carryover between wash and rinse cycles
- Fill and Dump design disposes of dirty water, replacing it with a fresh water rinse every cycle
- Field convertible from straight to corner and corner to straight for flexible installations and applications (kit required)
- 17-1/4" (438 mm) vertical inside clearance
- Built-in chemical pumps and priming switches
- Large removable scrap screen
- Durable stainless steel construction
- 1-year parts and labor warranty



Intertek



Intertek



*Racks per hour calculated with NSF suggested load time of five (5) seconds for door-type (straight thru)

TABLE DIMENSIONS CONNECTION TO DISHMACHINE

LEGEND
 A - Electrical Connection (1 1/8" Hole)
 B - Water Inlet (1/2" NPT)
 C - Drain Connection (2" NPT)
 D - Chemical Connection (7/8" Hole)

All dimensions from the floor can be increased 1 1/8" using the machine's adjustable feet.

MODEL NO.	MACHINE DIMENSIONS				DRAIN HEIGHT	SHIPPING INFORMATION					
	HEIGHT	WIDTH	WIDTH BETWEEN DISHTABLES	DEPTH		WEIGHT	CLASS	CUBE	HEIGHT	WIDTH	DEPTH
Conservor® XL-E	68-1/2" (1740 mm)	30-3/8" (773 mm)	25-1/4" (641 mm)	29-1/2" (750 mm)	8-7/8" (224 mm)	230 lbs (105 kg)	300	58.15 cu. ft.	72-1/2" (1842 mm)	33" (838 mm)	42" (1067 mm)

DIMENSIONS		WATER	
Wall Clearance (minimum)	4" (102 mm)	Inlet Temperature	120 °F min. (49 °C); 140 °F (60 °C) recommended
Standard Table Height	34" (864 mm)	Gallons per Hour	41.82 gal (158.31 L)
Inside Clearance	17-1/4" (438 mm)	Gallons per Hour**	39.78 gal (150.58 L)
Machine Height with Door Open	78" (1981 mm)	Gallons per Rack	1.02 gal (3.9 L)

OPERATING CAPACITY		ELECTRICAL REQUIREMENTS	
Racks per Hour	41 (39)*	Power Supply	Total Load
Dishes per Hour	1,025	Minimum Circuit Ampacity	Maximum Overcurrent Protection
Glasses per Hour	1,476	115/60/1	10.0 A
		230/60/1	5.0 A
			12.5 A
			20 A
			6.3 A
			15 A

OPERATING CYCLE (seconds)					
Wash	42	Rinse	25	Total Cycle	87

OPERATING TEMPERATURES	
Wash	120 °F min. (49 °C); 140 °F (60 °C) recommended
Rinse	120 °F min. (49 °C); 140 °F (60 °C) recommended

WASH PUMP MOTOR	
Wash Pump	1 HP

**Racks per hour calculated with NSF suggested load time of five (5) seconds for door-type (straight thru)
 **Gallons per hour calculated with NSF suggested load time of five (5) seconds for door-type (straight thru)*

Jackson WWS, Inc.

Shipping Address: 6209 North U.S. Highway 25E, Gray, KY 40734

Mailing Address: P.O.Box 1060, Barbourville, KY 40906

Telephone: 888-800-5672 • Fax: 606-523-1799

Email: info@jacksonwws.com

07610-004-00-91 [06/10/21]

www.jacksonwws.com