



BLS-4FLD-1H

XAKHT-HCFS: Full Size Ventless Hood for LED/TOUCH Convection Ovens

Water Connection is required for proper installation, filtration is highly recommended to prevent scale build up. Drain line or floor drain is needed.




UL 710 Emissions



Water Consumption Note* 10.3 oz from 3 hours and 30 minutes from the baking cycle. Therefore you would need to put the water consumption at less than 3 oz per hour.

LED digital programmable controls:



3 BAKING STEPS

0-20-40-60-80-100% HUMIDITY



2 FAN SPEEDS



0 - inf TIMER



120° - 500° F TEMPERATURE



PROOFER CONTROL



99 PROGRAMS 12 QUICK ACCESS



NEMA 6-50P Plug



OST-195-C Heavy-Duty Stand with Wheels

- Handles 10 full size sheet pans (not included)
- Aluminum

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy • NSF, MET to UL & CSA Standards
We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

Bakerlux Station Includes:

Model	Color	Volts	Watts	Amps	Unit Dimensions
XAFT-04FS-LD	Stainless	208-240	7600	32	w:31 1/2", h:19 5/8", d:35 1/2"
OST-195-C	Stainless	N/A			w:30" h:40 x d:27
XAKHT-HCFS	Stainless	208/240	200	1	w:31", h:10", d:34"



Shipping Unit Dimensions

1 Skid 305lbs
48 L x 40 W x 55 H