



BLS-4HTD-2H


Half Size Ventless Hood LED/TOUCH Ovens



UL 710 Emissions



TOUCH digital programmable controls:



- 9**
9 BAKING STEPS
- 0 - inf
TIMER
- 120° - 500° F
TEMPERATURE
- 0-20-40-60-80-100%
HUMIDITY
- 2
FAN SPEEDS
- PROOFER
CONTROL
- 99 PROGRAMS
- WI-FI
- DATA DRIVEN
COOKING -
CHAIN BASED
APPLICATION



OST-34A-CS Short Heavy-Duty Stand with Wheels for Half Size Ovens

- Handles 5 half size sheet pans (not included)
- Can hold 2 half size Cadco ovens with optional CXC651 Stacking Kit
- Aluminum



Made to Cadco specifications by UNOX S.p.A., Italy NSF, MET to UL & CSA Standards
Cadco Model XAFT-03HS-LD = UNOX Model XAFT-03HS-ELD-V-US

We recommend that the end user have a standard ice-machine filter when using a humidity hookup.

Bakerlux Station Includes:



Model	Color	Volts	Watts	AMPS	Unit Dimensions
XAKHT-HCHS	Stainless	208/240	200	1	W: 23 5/8" H: 10 7/8" D: 28 25/32"
XAFT-04HS-TD	Stainless	208/240	3800	16	W: 23 5/8" H: 19 5/8" D: 29"
OST-034A-CS	Stainless	N/A	N/A	N/A	W: 23.87" H: 21.15" D: 27.01"

Shipping Unit Dimensions

- 2 SKIDS CLASS 200
- 1 SKID 48X40X35 175 POUNDS- 1 OVEN & HOOD
- 1 SKID 48X40X52 145 POUNDS – 1 OVEN, STAND & STACKING KIT