



Stainless design.  
Stellar performance.  
Superior value.

Project name: \_\_\_\_\_

Location: \_\_\_\_\_

Item #: \_\_\_\_\_ QTY: \_\_\_\_\_

Model #: \_\_\_\_\_

# AF23

FREEZER

## SINGLE DOOR REACH-IN FREEZER



### AF23

- ▶ Tested to NSF Standard 7 requirements for open food storage.
- ▶ Standard with full two year parts and labor warranty and a five year compressor warranty.
- ▶ Arctic Air products must pass numerous quality control inspections throughout the manufacturing process.
- ▶ All products are pressurized with environmentally friendly and more efficient Hydrocarbon gas.
- ▶ Energy Star Approved



COMMERCIAL FREEZERS & REFRIGERATORS

Division of Broich Enterprises, Inc. 7550 Market Place Dr Eden Prairie, MN 55344  
952-941-2270 Fax: 952-941-3066 www.arcticairco.com info@arcticairco.com



Intertek



Intertek



# AF23 FREEZER

## SINGLE DOOR REACH-IN FREEZER

Electronic thermostat with external digital LED display for accurate control and easy reading.

Interior cabinet is bright white aluminum liner with full stainless steel floor with coved corners.

Three adjustable, heavy-duty epoxy coated wire shelves.

Self-contained capillary tube system using environmentally friendly R290 Hydrocarbon gas.


Exterior cabinet construction consists of full stainless steel front and sides.

Efficient condensate hot gas loop built into condensate pan for energy saving evaporation of excess condensate water.

Bottom mounted compressor for more efficient operation in coolest area of kitchen.

Front accessible, bottom mounted condensing unit is mounted on slide out rack for easy maintenance.

Easy to mount plate casters (two lockable) are standard with all units.



Vaulted self closing doors that remain open at 90 degrees.

Freezer door frame has integral factory installed heating element to eliminate condensation.

Magnetic door gasket is removable and replaceable without tools.

Field reversible, lockable door with foamed-in-place recessed handle.

Larger fan motors and blades for more efficient air flow ensuring faster recovery times.

Unit holds full size sheet pans front to back. With optional s/s Pan Slide rack (#64900K). Some field install is required.

- ▶ Tested to NSF Standard 7 requirements for open food storage.
- ▶ Standard with full two year parts and labor warranties and a five year compressor warranty.

### STAINLESS STEEL DESIGN • STELLAR PERFORMANCE • SUPERIOR VALUE

Model Number	External Dimensions			Doors	Epoxy Coated Shelves (horizontal)	Cubic Feet	Temperature Range	Cord Length	HP	AMPS	REF	NEMA Plug	Crate Weight
	Width	Depth	Height*										
AF23	26.75"	32.75"	82.75"	1	3	23	-10°F to 10°F	8'	4/5	8.0	R290	5-15P	325Lbs

Depth with door open 90° = 59.50"

\*Height includes 6" for casters

