



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Royal Series Multi Station

Royal Series Underbar



KR19-M36R-10 shown without optional Speedrail

STANDARD FEATURES

- **Interior**
20 gauge stainless steel. 12" deep Ice Bin section. 10" deep Bottle section, wire bottle racks included
- **Front Apron**
20 gauge stainless steel clad over 20 gauge galvanized steel
- **Sides**
20 gauge stainless steel
- **Backsplash**
20 gauge stainless steel
- **Back and Bottom**
20 gauge galvanized steel
- **Legs**
1-5/8" tubular 16 gauge stainless steel with grey plastic bullet foot
- **Tube Access (Cold Plate)**
3/4" x 3-1/2" cutout in left side of backsplash
- **Insulation**
Foamed-in-place polyurethane
- **Plumbing**
Cold Plate: 1/2" IPS drain connection
No Cold Plate: 1" IPS drain connection
- **NOTE:** Cold Plate units supplied with 1/2" x 4" male threaded PVC tailpipe

OPTIONAL ACCESSORIES

- KR-101 - Condiment Tray
- KR-103 - Stainless Steel Divider
- KR-310 - Right End Splash
- KR-311 - Left End Splash
- SC"XX"H - Partial Sliding Cover ("XX" denotes size of Ice Bin)
- SC"XX"F - Full Sliding Cover ("XX" denotes size of Ice Bin)
- KR-401 - Cap Catcher and Opener
- KR-406 - Faucet installed over Ice Bin for Meltdown
- KR-501 - Towel Ring
- KR-502 - 15" Deep Liner on Ice Bin Section

OPTIONAL FEATURES

- **Cold Plate**
Cast aluminum post mix plate with 10 circuits. Plate is sealed into bottom. Each circuit is 5/16" OD stainless steel tubing. Two full with remainder to be half circuits. Bump and swedge fittings on ends

Top View

Front View

| Model Numbers | Overall Length A | Ice Bin Length B | Ice Bin Location | Bottles Stored | Left Side to Ice Bin Drain C | Ice Capacity (lbs.) | Cold Plate Circuits | Weight (lbs.) |
|---------------|---------------------|---------------------|------------------|----------------|---------------------------------|---------------------|---------------------|---------------|
| KR19-M36R | 3'-0" | 24" | Right | 6 | 24" | 80 | N/A | 95 |
| KR19-M36L | 3'-0" | 24" | Left | 6 | 12" | 80 | N/A | 95 |
| KR19-M36R-10 | 3'-0" | 24" | Right | 6 | 24" | 80 | 10 | 172 |
| KR19-M36L-10 | 3'-0" | 24" | Left | 6 | 12" | 80 | 10 | 172 |
| KR19-M42R | 3'-6" | 30" | Right | 6 | 27" | 97 | N/A | 108 |
| KR19-M42L | 3'-6" | 30" | Left | 6 | 15" | 97 | N/A | 108 |
| KR19-M42R-10 | 3'-6" | 30" | Right | 6 | 27" | 97 | 10 | 185 |
| KR19-M42L-10 | 3'-6" | 30" | Left | 6 | 15" | 97 | 10 | 185 |
| KR19-M48C | 4'-0" | 24" | Center | 12 | 24" | 80 | N/A | 116 |
| KR19-M48R | 4'-0" | 36" | Right | 6 | 30" | 115 | N/A | 116 |
| KR19-M48L | 4'-0" | 36" | Left | 6 | 18" | 115 | N/A | 116 |
| KR19-M48C-10 | 4'-0" | 24" | Center | 12 | 24" | 80 | 10 | 193 |
| KR19-M48R-10 | 4'-0" | 36" | Right | 6 | 30" | 115 | 10 | 193 |
| KR19-M48L-10 | 4'-0" | 36" | Left | 6 | 18" | 115 | 10 | 193 |

Conforms to NSF St. 2