



Model: _____ Item #: _____ Date: _____

Project: _____ Qty: _____ Approved By: _____

Deck Mount Pitcher & Glass Fillers

Royal Series Plumbing



Standard Features

- Adjustable flow outlet (0.25 GPM - 1.5 GPM)
- Latch for continuous on position
- Push-back water activation
- Pedestal with adjustable flange
- 1/2" NPS male inlet
- 20-125 PSI pressure
- Chrome plated brass
- Fits in 7/8" hole

Product Compliance

- NSF-61 & NSF/ANSI 372
- ASME A112.18.1-2012/CSA B125.1-12
- Massachusetts Approved



Repair Kit for Pitcher & Glass Fillers (model 16-136L)



- Used on Glass Filler (16-135L) or Pitcher Fillers (16-137L, 16-138L, 16-139L)
- Repairs latch mechanism to avoid replacing entire faucet

Model	Deck to Spout Tip (A)	Deck to Push Lever (B)	Deck to Top (C)	Overall Height (D)
16-135L	8"	4-15/16"	9-5/8"	11-5/8"
16-137L	10"	6-15/16"	11-5/8"	13-5/8"
16-138L	12"	8-15/16"	13-5/8"	15-5/8"
16-139L	14"	10-15/16"	15-5/8"	17-5/8"

WARNING:

Plumbing connections should be made by qualified personnel who will observe all applicable plumbing, sanitary and safety codes.

California Prop 65 Warning:

This product can expose you to chemicals including lead and lead compounds, which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

