



## Camshelving® Premium Series

### Mobile Drying and Storage Racks 3 Tiers – Vertical

HEIGHT	DEPTH	LENGTHS
1	1	2
1910 mm	610 mm	1220 mm 1525

### 4 Tiers – Angled

HEIGHT	DEPTH	LENGTH
1	1	1
1910 mm	610 mm	1220 mm

### 5 Tiers – Dome

HEIGHT	DEPTHS	LENGTH
1	2	1
1910 mm	540 mm 610	915 mm

- **Vertical Drying and Storage Rack includes:**  
2 factory assembled mobile post kits, 6 shelf traverses, 12 or 15 vertical drying cradles and 4 premium swivel casters with total locking brake. 1220 mm long - ships in 5 cartons. 1525 mm long - ships in 6 cartons.
- **Angled Drying and Storage Rack includes:**  
2 factory assembled mobile post kits, 8 shelf traverses, 16 angled drying cradles and 4 premium swivel casters with total locking brake. Ships in 5 cartons.
- **Dome Drying and Storage Rack includes:**  
2 factory assembled mobile post kits, 10 shelf traverses, 10 dome drying cradles and 4 premium swivel casters with total locking brake. Ships in 3 cartons.

#### Features & Benefits

- Promote sanitary drying, safe handling and efficient product organization with easy access to product. The Vertical Drying and Storage Rack can be used for trays, cutting boards, lids, and/or baking sheet pans. Store up to 100 patient meal delivery domes or plate covers upright in the Dome Drying and Storage Rack. Use the Angled Drying and Storage Rack to securely hold a variety of food pans, pots, bowls and other kitchen wares or patient meal delivery pellets.
- Ideal for use in all commercial and non-commercial kitchens including warewashing areas.
- Posts and traverses have a steel core and smooth polypropylene exterior for superior strength and durability. Traverse dovetails are molded into posts. NOTE: Mobile units require Mobile Posts for assembly.
- Premium caster is made of highly durable, non-corrosive plastic with a 127 mm swivel, non-marking thermoplastic rubber wheel. Total locking brake locks both swivel motion and the wheel.
- Optional donut bumper offers added protection during transport and when maneuvering mobile units into place against walls or alongside other units for storage.
- Drying and Storage Cradles install directly onto shelf traverses. Made of highly durable ABS plastic. Dishwasher safe.

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_



Vertical Drying and Storage Rack



Angled Drying and Storage Rack



Dome Drying and Storage Rack

## PREMIUM SERIES WEIGHT BEARING CAPACITY

Weight must be evenly distributed across the entire shelf.

	UNIT LENGTH 765 - 1525 mm
<b>MOBILE UNIT</b> Unit only*	340 kg

\* Due to the weight bearing capacity of casters, maximum weight load on an entire Mobile Unit is 340 kg.

- Uniquely engineered Post Connectors offer exceptional cross stabilization. Weight bearing is uncompromised.
- Posts and traverses easily wipe clean. Traverses can be removed and adjusted at 10,2 cm increments.
- Requires some assembly with minimal parts. Use a rubber mallet only.
- Lifetime warranty against rust and corrosion (posts, traverses and cradles).
- Available in 1 color – Speckled Gray (480).

#### Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

Information and specifications are subject to change without notice. Please confirm at time of order.

CAMBRO U.S.A.  
TEL: 1(714) 848-1555  
FAX: 1(714) 230-4375  
international@cambro.com

**CAMBRO**  
TRUSTED FOR GENERATIONS™  
www.cambro.com

© Copyright Cambro Manufacturing Company. Printed in the U.S.A. REV. 10/18

# Camshelving® Premium Series

## Mobile Drying and Storage Racks

3 Tiers – Vertical

4 Tiers – Angled

5 Tiers – Dome

Project \_\_\_\_\_

Item No. \_\_\_\_\_

Model No. \_\_\_\_\_

Quantity \_\_\_\_\_

## 1910<sub>mm</sub> Vertical Drying and Storage Rack

HEIGHT

610<sub>mm</sub>  
DEPTH

CODE	DIMENSIONS D x L x H	SLOT SPACE	HOLDING CAPACITY
CPMU244875DRPKG	610 x 1220 x 1910 mm	33 mm	84 Trays
CPMU246075DRPKG	610 x 1525 x 1910	33	105 Trays

**Color:** Speckled Gray (480).

1220 mm unit ships in 5 cartons. 1525 mm unit ships in 6 cartons.



## Angled Drying and Storage Rack

610<sub>mm</sub>  
DEPTH

CODE	DIMENSIONS D x L x H	SLOT SPACE	HOLDING CAPACITY
CPMU244875PDPKG	610 x 1220 x 1910 mm	60 mm	128 Pellets and Bases or 16 GN 1/1 Food Pans

**Color:** Speckled Gray (480).

Ships in 5 cartons.



## Dome Drying and Storage Rack

540<sub>mm</sub>  
DEPTH

CODE	DIMENSIONS D x L x H	SLOT SPACE	HOLDING CAPACITY
CPMU213675DDPKG	540 x 915 x 1910 mm	78 mm	100 Domes

**Color:** Speckled Gray (480).

Ships in 3 cartons.

610<sub>mm</sub>  
DEPTH

CODE	DIMENSIONS D x L x H	SLOT SPACE	HOLDING CAPACITY
CPMU243675DDPKG	610 x 915 x 1910 mm	78 mm	100 Domes

**Color:** Speckled Gray (480).

Ships in 3 cartons.



### Optional Accessories

- Donut Bumper
- Shelf Identification Tags
- Shelf Rails

### Architect Specs

Posts and Traverses: Internal steel core, reinforced polypropylene exterior.

Post Connectors: Reinforced polypropylene.

Drying Cradles: High impact ABS material.

Caster: Non-corrosive plastic body and brake with non-marking thermoplastic rubber wheel.

### Approvals



Post Connectors, Corner Connectors, Seismic Foot, Wall Fastener, Identification Tags, Security Cages, Single Shelf Sheet Pan/Tray Rack, Shelf Rails, Divider Bars, High Density Track and Extension Kits are not NSF Listed.

**CAMBRO**  
TRUSTED FOR GENERATIONS™  
www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.

CAMBRO U.S.A.  
TEL: 1(714) 848-1555  
FAX: 1(714) 230-4375  
international@cambro.com

CPPM9

© Copyright Cambro Manufacturing Company. Printed in the U.S.A. REV. 10/18

1001801