



BLS-4FLD-2H

XAKHT-HCFS: Full Size Ventless Hood for LED/TOUCH Convection Ovens

Water Connection is required for proper installation, filtration is highly recommended to prevent scale build up. Drain line or floor drain is needed.



UL 710 Emissions



Water Consumption Note* 10.3 oz from 3 hours and 30 minutes from the baking cycle. Therefore you would need to put the water consumption at less then 3 oz per hour.

LED digital programmable controls:



- 3 BAKING STEPS
- 0 - inf TIMER
- 120° - 500° F TEMPERATURE
- 0-20-40-60-80-100% HUMIDITY
- 2 FAN SPEEDS
- PROOFER CONTROL
- 99 PROGRAMS
12 QUICK-ACCESS



Full Size
4 Shelves - per oven
Heavy-Duty Digital
18x26 Sheet pans

Made to Cadco Ltd. specifications by UNOX S.p.A., Italy • NSF, MET to UL & CSA Standards
We recommend that the end user have a standard ice-machine filter when using a humidity hookup.



OST-195-CS

Short Heavy-Duty Stand with Wheels for Full Size Ovens

- Handles 5 full size sheet pans (not included)
- Can hold 2 full size Cadco ovens with Stacking Kit
- Aluminum

Bakerlux Station Includes:

Model	Color	Volts	Watts	Amps	Unit Dimensions
XAFT-04FS-LD	Stainless	208-240	7600	32	w:31 1/2", h:19 ^{5/8} ", d:35 ^{1/2} "
OST-195-C	Stainless	N/A			w:30" h:40 x d:27
XAKHT-HCFS	Stainless	208/240	200	1	w:31 " , h:10 " , d:34"

Shipping Unit Dimensions

2 SKIDS CLASS 200

1 SKID 44X38X56 260 POUNDS -1 OVEN ,HOOD AND STAND
1 SKID 44X38X29 200 POUNDS - 1 OVEN AND STACKING KIT

