



# MODULAR (48")



## AIR COOLED



### IM-1700, IM-2000

MODEL	STORAGE BIN OPTION	DIMENSION (WxDxH)	WEIGHT	ICE SHAPE
		inch	lbs (Net / Shipping)	
IM-1700-AC	IB-085-48, Kloppenberg	48 x 24.5 x 30.4	322 / 366	CUBE
IM-1700-AH				HALF CUBE
CONDENSER	ELECTRICAL	Power (kWh/100 lbs ice)	Air / Water 70°F / 50°F	Air / Water 90°F / 70°F
Air Cooled	208~230 V/60 Hz/1 Ph	4.66	1722 lbs	1446 lbs
MODEL	STORAGE BIN OPTION	DIMENSION (WxDxH)	WEIGHT	ICE SHAPE
		inch	lbs (Net / Shipping)	
IM-2000-AC	IB-085-48, Kloppenberg	48 x 24.5 x 30.4	322 / 366	CUBE
IM-2000-AH				HALF CUBE
CONDENSER	ELECTRICAL	Power (kWh/100 lbs ice)	Air / Water 70°F / 50°F	Air / Water 90°F / 70°F
Air Cooled	208~230 V/60 Hz/1 Ph	4.24	2032 lbs	1708 lbs

## WATER COOLED



### IM-1700, IM-2000

MODEL	STORAGE BIN OPTION	DIMENSION (WxDxH)	WEIGHT	ICE SHAPE
		inch	lbs (Net / Shipping)	
IM-1700-WC	IB-085-48, Kloppenberg	48 x 24.5 x 30.4	311 / 379	CUBE
IM-1700-WH				HALF CUBE
CONDENSER	ELECTRICAL	Power (kWh/100 lbs ice)	Air / Water 70°F / 50°F	Air / Water 90°F / 70°F
Water Cooled	208~230 V/60 Hz/1 Ph	2.95	1843 lbs	1678 lbs
MODEL	STORAGE BIN OPTION	DIMENSION (WxDxH)	WEIGHT	ICE SHAPE
		inch	lbs (Net / Shipping)	
IM-2000-AC	IB-085-48, Kloppenberg	48 x 24.5 x 30.4	322 / 366	CUBE
IM-2000-AH				HALF CUBE
CONDENSER	ELECTRICAL	Power (kWh/100 lbs ice)	Air / Water 70°F / 50°F	Air / Water 90°F / 70°F
Water Cooled	208~230 V/60 Hz/1 Ph	4.24	2032 lbs	1708 lbs

## REMOTE



### IM-1700, IM-2000

MODEL	STORAGE BIN OPTION	DIMENSION (WxDxH)	WEIGHT	ICE SHAPE
		inch	lbs (Net / Shipping)	
IM-1700-RC	IB-085-48, Kloppenberg	48 x 24.5 x 30.4	322 / 366	CUBE
IM-1700-RH				HALF CUBE
CONDENSER	ELECTRICAL	Power (kWh/100 lbs ice)	Air / Water 70°F / 50°F	Air / Water 90°F / 70°F
Air Cooled	208~230 V/60 Hz/1 Ph	4.44	1680 lbs	1462 lbs
MODEL	STORAGE BIN OPTION	DIMENSION (WxDxH)	WEIGHT	ICE SHAPE
		inch	lbs (Net / Shipping)	
IM-2000-RC	IB-085-48, Kloppenberg	48 x 24.5 x 30.4	322 / 366	CUBE
IM-2000-RH				HALF CUBE
CONDENSER	ELECTRICAL	Power (kWh/100 lbs ice)	Air / Water 70°F / 50°F	Air / Water 90°F / 70°F
Air Cooled	208~230 V/60 Hz/1 Ph	4.04	1980 lbs	1730 lbs



### Condensing Unit (pre-charged)

MODEL	ELECTRICAL	DIMENSION (WxDxH)	WEIGHT
		inch	lbs (Net / Shipping)
IRC-2000	wired to machine head (50' power cable included with each line-set)	22.6 x 35.6 x 27.1	143 / 195

### Tubing (pre-charged)



IRT-20R410A (20ft with Quick connects)  
IRT-35R410A (35ft with Quick connects)  
IRT-50R410A (50ft with Quick connects)