

EO SERIES - BOILERLESS | *Low Volume; Low Maintenance.*

STANDARD FEATURES:

CONNECTIONLESS:

- Boilerless design for ease of use and low maintenance
- No water connection required – manual fill
- High-efficiency steam control is ENERGY STAR® certified
- Rapid cooking with no fans or moving parts
- Professional controls with 60-minute timer, buzzer and constant steam feature
- Illuminated power switch with low water and cook lights
- Stainless steel exterior and cooking compartment
- Heavy-duty door and latch mechanism
- Long-life door gasket with exclusive Vulcan pan guard
- Manual drain lever and flexible drain hose for easy positioning

AUTO-FILL - WATER LINE CONNECTION:

Same features as standard steamer, plus:

- Water line connection for automatic water fill / refill
- Electronic level sensing with no moving parts
- Overfill sensor with water shut-off and buzzer



C24E05
5-Pan Capacity



C24E03
3-Pan Capacity



EO SERIES - BOILERLESS | ELECTRIC

Model	Pan Capacity*	Input	Standard Power Supply
CONNECTIONLESS			
C24E03	3	8 kW	208V, 50-60 Hz, 3 Phase
C24E05	5	12 kW	208V, 50-60 Hz, 3 Phase
WITH AUTO-FILL WATER LINE CONNECTION			
C24E03AF	3	8 kW	208V, 50-60 Hz, 3 Phase
C24E05AF	5	12 kW	208V, 50-60 Hz, 3 Phase

NOTE: Can be field converted to: 208V, 60-50 Hz, 1 Phase | 240V, 60-50 Hz, 3 Phase | 240V, 60-50 Hz, 1 Phase.

*12" x 20" x 2½" Pan

EA SERIES - PLUS | À la Carte Steamer with Enhanced Features.

Accelerate your kitchen with faster startup and continuous steam generation for nonstop cooking performance with Smart Fill technology.

STANDARD FEATURES:

- Professional controls with 60-minute timer, buzzer and constant steam feature, cook/ready lights and power switch
- Stainless steel exterior and stainless steel cooking compartments with coved interior corners
- Heavy duty door and latch mechanism
- Long-life door gasket with exclusive Vulcan pan guard
- Split water line connection
- External delimiting port
- Staged water fill for superior heat-up and steam quality
- High output stainless steel generator with auto SmartDrain™ & PowerFlush™ System



C24EA3 PLUS
3-Pan Capacity



C24EA5 PLUS
5-Pan Capacity

EA PLUS | ELECTRIC

Model	Pan Capacity*	Input	Standard Power Supply
C24EA3 PLUS	3	8.5 kW	208V, 50-60 Hz, 3 Phase
C24EA5 PLUS	5	15 kW	208V, 50-60 Hz, 3 Phase

NOTE: Can be field converted to: 208V, 60-50 Hz, 1 Phase | 240V, 60-50 Hz, 3 Phase | 240V, 60-50 Hz, 1 Phase.

**12" x 20" x 2½" Pan*



View operational video