STEAMERS - COUNTER VULCAN

COUNTERTOP STEAMERS | *A Full Range Delivering Spectacular Results.*

When floor space is at a premium, Vulcan countertop steamers offer a solution. These countertop steamers are ideal for a variety of foods, including vibrant veggies, succulent seafood and perfectly cooked proteins.

EO Boilerless Low Maintenance	EA Plus Enhanced Features	PowerSteam [*] High Productivity		w Water Energy) ligh Efficiency
FEATURES / SPECS	EO Boilerless C24EO3 / AF	EA Plus C24EA3 PLUS	PowerSteam [™] C24EA3 PS	LWE C24EA3 LWE
	C24EO5 / AF	C24EA5 PLUS	C24EA5 PS	C24EA5 LWE
High-Efficiency Steam Generato (Patent Pending)	or N/A	\checkmark	\checkmark	\checkmark
Professional Controls with 60-Minute Timer, Buzzer and Constant Steam Feature, Cook/ Ready Lights and Power switch	√	\checkmark	\checkmark	\checkmark
Two-Speed Staged Water Fill	N/A	\checkmark	\checkmark	\checkmark
No Water Connection Required	\checkmark	N/A	N/A	N/A
Automatic SmartDrain & PowerFlush™ System	N/A	\checkmark	\checkmark	\checkmark
235°F Steam for 20% Faster Cooking Time	N/A	N/A	\checkmark	N/A
ENERGY STAR [®] Certified	\checkmark	N/A	N/A	\checkmark
Uses 90% Less Water and 50% Less Energy Versus Traditional Units	N/A	N/A	N/A	\checkmark

VULCAN STEAMERS - COUNTER

EO SERIES - BOILERLESS | Low Volume; Low Maintenance.

STANDARD FEATURES:

CONNECTIONLESS:

- Boilerless design for ease of use and low maintenance
- No water connection required manual fill
- High-efficiency steam control is ENERGY STAR[®] certified
- · Rapid cooking with no fans or moving parts
- Professional controls with 60-minute timer, buzzer and constant steam feature
- Illuminated power switch with low water and cook lights
- Stainless steel exterior and cooking compartment
- Heavy-duty door and latch mechanism
- Long-life door gasket with exclusive Vulcan pan guard
- Manual drain lever and flexible drain hose for easy positioning

AUTO-FILL - WATER LINE CONNECTION:

Same features as standard steamer, plus:

- Water line connection for automatic water fill / refill
- · Electronic level sensing with no moving parts
- Overfill sensor with water shut-off and buzzer





C24EO5 5-Pan Capacity

C24EO3 3-Pan Capacity



EO SERIES - BOILERLESS | ELECTRIC

Model CONNECTIONLESS	Pan Capacity*	Input	Standard Power Supply
C24EO3 C24EO5	3 5	8 kW 12 kW	208V, 50-60 Hz, 3 Phase 208V, 50-60 Hz, 3 Phase
WITH AUTO-FILL WATER	R LINE CONNECTION		
C24EO3AF C24EO5AF	3 5	8 kW 12 kW	208V, 50-60 Hz, 3 Phase 208V, 50-60 Hz, 3 Phase

NOTE: Can be field converted to: 208V, 60-50 Hz, 1 Phase | 240V, 60-50 Hz, 3 Phase | 240V, 60-50 Hz, 1 Phase. *12" x 20" x 2½" Pan