KETTLES - FULLY JACKETED VULCAN



FULLY JACKETED A True Workhorse for Over 50 Years. Durable, Efficient and Reliable.

STANDARD FEATURES:

- · Heavy 11-gauge rim
- Faucet bracket
- · 316 stainless steel liner
- Sloped bottom for superior draining
- Splash-proof housing with on/ off switch and warm/simmer/ boil control
- 2" plug draw-off valve with perforated strainer
- · Spring assist cover with condensate ring
- Heavy duty pivot assembly for kettle cover, yolk style mount with tie bar.
- · Electronic ignition
- 15 psi



GAS KETTLES | STATIONARY

| Model | Capacity | Input |
|---------|----------|----------------|
| GS40ES* | 40 Gal | 135,000 BTU/hr |
| GS60E | 60 Gal | 135,000 BTU/hr |
| GL80E | 80 Gal | 135,000 BTU/hr |
| GT100E | 100 Gal | 135,000 BTU/hr |
| GT125E | 125 Gal | 135,000 BTU/hr |
| GT150E | 150 Gal | 135,000 BTU/hr |

^{*}GS40ES comes as a short height configuration.

ELECTRIC KETTLES | STATIONARY

| Model | Capacity | Input | |
|-------|----------|-------|--|
| EL80 | 80 Gal | 36 kW | |
| ET100 | 100 Gal | 36 kW | |
| ET125 | 125 Gal | 36 kW | |
| ET150 | 150 Gal | 36 kW | |

DIRECT STEAM KETTLES | STATIONARY

| Model | Capacity | Input | |
|-------|----------|---------|--|
| SL80 | 80 Gal | 3.4 BHP | |
| ST100 | 100 Gal | 4 BHP | |
| ST125 | 125 Gal | 5 BHP | |
| ST150 | 150 Gal | 6 BHP | |