

KETTLES - 2/3 JACKETED

K SERIES - GAS FLOOR MOUNTED | *Ellipsoidal Bottom for Superior Heat Transfer.*

STANDARD FEATURES:

- True working capacity
- Embossed gallon/liter markings
- Heavy bar rim
¼" x ⅝" 20-gallon
⅜" x 1" 40- or 60-gallon
- Splash-proof housing with on/off switch and intuitive warm/simmer/boil control
- Faucet bracket
- High-efficiency gas power burner with electronic ignition
- 115V cord and 3 prong plug
- 316 stainless steel liner

STATIONARY MODELS:

- 2" compression draw-off valve with perforated strainer
- Spring assist cover with condensate ring
- Heavy duty pivot assembly for kettle cover, yolk style mount with tie bar



K40GL

Stationary model shown with optional DOV PLUG2 draw-off valve.

K SERIES GAS | STATIONARY & TILTING MODELS

Model	True Working Capacity	Input
STATIONARY		
K20GL	20 Gal	100,000 BTU/hr
K40GL	40 Gal	100,000 BTU/hr
K60GL	60 Gal	100,000 BTU/hr
TILTING		
K20GLT	20 Gal	100,000 BTU/hr
K40GLT	40 Gal	100,000 BTU/hr
K60GLT	60 Gal	100,000 BTU/hr

NOTE: Spring assist cover is an accessory for tilting kettles.



K40GLT

Tilting model shown with optional DOV PLUG2 draw-off valve.

COMPATIBLE FAUCETS



SGLTS 18NZLJ



DBLTS 18NZLJ



DBLPTS POTFIL



DBFCTS WSHDWN



DBPTYTS WSHDWN