# KETTLES - 2/3 JACKETED VULCAN



## K SERIES - DIRECT STEAM FLOOR MOUNTED

#### **STANDARD FEATURES:**

- · True working capacity
- Embossed gallon/liter markings
- · Heavy bar rim ¼" x %" 20-gallon %" x 1" 40- or 60-gallon
- Faucet bracket
- 316 stainless steel liner
- · Steam control assembly including inlet globe valve and steam trap, condensate strainer and check valve

#### STATIONARY MODELS:

- 2" compression draw-off valve with perforated strainer
- · Spring assist cover with condensate ring
- · Heavy duty pivot assembly for kettle cover, yolk style mount with tie bar



## K SERIES DIRECT STEAM | STATIONARY & TILTING MODELS

	STATIONARY			TILTING	
Model	<b>True Working Capacity</b>	Input	Model	<b>True Working Capacity</b>	Input
K20DL	20 Gal	1 BHP	K20DLT	20 Gal	1 BHP
K40DL	40 Gal	1.5 BHP	K40DLT	40 Gal	1.5 BHP
K60DL	60 Gal	2.3 BHP	K60DLT	60 Gal	2.3 BHP

NOTE: Spring assist cover is an accessory for tilting kettles.

See 111 for conversion rate.

#### **GALLONS MARKING**

6 GAL	2, 3, 4, 5, 6
12 GAL	6, 8, 10, 12

20 GAL 10, 12, 14, 16, 18, 20 40 GAL 15, 20, 25, 30, 35, 40

60 GAL 20, 25, 35, 40, 45, 50, 55, 60



#### **COMPATIBLE FAUCETS**











**DBFCTTS WSHDWN** 

**DBPTYTS WSHDWN** 



# VULCAN KETTLES - 2/3 JACKETED

# K SERIES - FLOOR MOUNTED | OPTIONS

#### **ALL ELECTRIC MODEL FACTORY-INSTALLED OPTIONS:**

220V, 50-60 Hz, 1 Phase (Gas) 480V, 60 Hz, 3 Phase (3 Wire)

380V, 3 Phase 415V, 3 Phase 440V, 3 Phase

### **STATIONARY KETTLES ONLY | FACTORY-INSTALLED OPTIONS:**

**Security Features:** 

**SK-PPS** Electric and gas stationary kettle security screws, tack welds and

controls protected by lockable cover (lock by others); Draw-off

valve secured with chain; perforated flue cover

(gas only)

Direct stationary steam kettle security screws, tack welds, draw-SKD-PPS

off valve secured with chain

**LKCOVER-PPS** Cover with lock hasp, lock by others

Protection for draw-off valve for K Series Stationary Kettles SKDOV PPS

**Draw-off Valves:** 

**KDOV COMP3\*** Compression draw-off valve, 3" in lieu of standard 2" valve

**KDOV PLUG2** Plug draw-off valve, 2" in lieu of standard 2" valve

## TILTING KETTLES ONLY | FACTORY-INSTALLED OPTIONS:

Motorized Power Tilt (Gas Only)

**Security Features:** 

TK-PPS Electric and gas tilting kettle without draw-off valve; security

> screws, tack welds and controls protected by lockable cover (lock by others); tilting handle secured with chain; perforated

flue cover

**TKD-PPS** Direct stationary steam kettle without draw-off valve; security

screws, tack welds

**KDOV CHAIN-PPS** Draw-off valve secured with chain only

Protection for draw-off valve for K Series with chain TKDOV PPS

**Draw-off Valves:** 

KTDOV COMP2 Compression draw-off valve, 2" with perforated strainer KTDOV COMP3\* Compression draw-off valve, 3" with perforated strainer\*

Plug draw-off valve, 2" with perforated strainer KTDOV PLUG2

\*20-gallon kettle not available with 3" draw-off valve.



Control Panel Cover



**SKDOV PPS** 



2" Compression



3" Compression



2" Plug