



STAINLESS STEEL CORNER TABLES

Item #: _____ Qty #: _____
 Model #: _____
 Project #: _____



FEATURES:

TOP furnished with 1 5/8" square bend edges on front and sides. 5" splash with a 1" return on rear.

Hat channels stud welded to reinforce and maintain a level working surface.

Front to Back Leg Stretchers bolted to legs and require assembly. Left to Right Stretchers welded to legs.

CONSTRUCTION:

All TIG welded. Exposed weld areas polished to match adjacent surfaces.

Entire top mechanically polished to a satin finish.

Top is sound deadened.

Roll formed embossed galvanized hat channels are secured to top by means of structural adhesive and weld studs.

Gussets welded to support hat sections.

5' length is standard on one side. Length can be modified, but not to exceed 7' on one wall dimension.

MATERIAL:

TOP: 14 gauge stainless steel type "304" series.

STRETCHERS: 1 5/8" dia. tubular stainless steel.

LEGS: 1 5/8" diameter tubular stainless steel.

Stainless steel gussets.

1" adjustable stainless steel bullet feet.

Optional Sinks: Fabricated sinks type "304" stainless steel.

Furnished with 1 1/2" IPS basket drain.

Faucets not included.

24" WIDE

Length	Model #	Wt.
60"	KTMS-245	240 lbs.
72"	KTMS-246	260 lbs.
84"	KTMS-247	280 lbs.
96"	KTMS-248	305 lbs.
108"	KTMS-249	330 lbs.
120"	KTMS-2410	355 lbs.
132"	KTMS-2411	375 lbs.
144"	KTMS-2412	400 lbs.

30" WIDE

Length	Model #	Wt.
60"	KTMS-305	320 lbs.
72"	KTMS-306	360 lbs.
84"	KTMS-307	400 lbs.
96"	KTMS-308	440 lbs.
108"	KTMS-309	000 lbs.
120"	KTMS-3010	520 lbs.
132"	KTMS-3011	560 lbs.
144"	KTMS-3012	600 lbs.

ACCESSORIES	Model #	Qty.
36" Width	KT-100	
Additional Length in excess of 5"	KT-101	
Special Sizing Charge	KT-102	
Stainless Steel Undershelf	KT-103	
Stainless Steel Cabinet Base	KT-104	
14 Gauge Unit	KT-105	

SINKS	Model #	Qty.
16" x 20" x 12"	TA-11B	
20" x 20" x 12"	TA-11D	
20" x 24" x 12"	TA-11E	



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Quotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DETAILS and SPECIFICATIONS

TOL \pm .500"

ALL DIMENSIONS ARE TYPICAL

