

Profit from the Eagle Advantage®

Specification Sheet

Short Form Specifications

Eagle Three-Compartment Sink, model_______, with 2"-wide "Euro-Style" edging on front and sides. Sink bowls are heavy gauge type 304 stainless steel, with 13½" water level, deep drawn, seamless and have all corners coved. Top—including backsplash, and drainboards (when required)—is heavy gauge type 430 stainless steel. Drainboards shall be "V" creased for positive drainage. 9½" high backsplash with 1" upturn and tile edge. Legs to be 1½" 0.D. galvanized tubing with front-to-back crossbracing, and 1" high impact plastic adjustable bullet feet.



Ontions	,	Accessories	
UDTIONS	,	Accessories	:

- ☐ Stainless steel legs
- ☐ Stainless steel bullet feet
- Lever drains
- ☐ Twist handle drains
- Twist drain brackets
- Faucets
- Sink covers

2"-WIDE

EDGING

EURO-STYLE

- ☐ Waste outlets
- ☐ Sink kits☐ Overflow hole

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 • 800-441-8440 • Fax: 302-653-2065

www.eaglegrp.com www.eaglegrpnews.com www.eaglemhc.com

For custom configuration or fabrication needs, contact our **SpecFAB® Division.** Phone: 302-653-3000 • Fax: 302-653-2065 • e-mail: guotes@eaglegrp.com

Item No.:	
Project No.:	
S.I.S. No.:	

414 Series Coved Corner Three-Compartment Sinks

MODELS:

414-16-3	□ 414-18-3	□ 414-22-3	414-24-3
414-16-3-18	□ 414-18-3-18	414-22-3-18	414-24-3-18
☐ 414-16-3-18L	☐ 414-18-3-18L	☐ 414-22-3-18L	☐ 414-24-3-18L
☐ 414-16-3-18R	☐ 414-18-3-18R	☐ 414-22-3-18R	☐ 414-24-3-18R
414-16-3-24	414-18-3-24	414-22-3-24	414-24-3-24
☐ 414-16-3-24L	☐ 414-18-3-24L	☐ 414-22-3-24L	☐ 414-24-3-24L
☐ 414-16-3-24R	☐ 414-18-3-24R	☐ 414-22-3-24R	☐ 414-24-3-24R

Materials

- Sink bowls: Heavy gauge type 304 stainless steel.
- Top: Drainboards, backsplash and euro-style edging are heavy gauge type 430 stainless steel.
- Legs: 1% (41mm)-diameter heavy-gauge galvanized tubing with plated 12-gauge gussets and high-impact corrosion resistant fully adjustable bullet feet - crossbracing is 1" (25mm)-diameter heavy-gauge galvanized tubing.

Design and Construction Features

- All bowls have deep-drawn one-piece seamless construction, using state-of-the-art hydraulic presses.
- Sink bowls have generous radius with minimum dimension of 3" (76mm) and are rectangular for maximum capacity.
- New 20" x 16" (508 x 406mm) bowl design, with enhanced polishing techniques.
- 13½" (343mm) water level is standard.
- Swirl-away drainage.
- Leg gusset assemblies welded adjacent to sink bowl for maximum weight support and stability.
- 9½" (241mm) standard backsplash includes 1" (25mm) upturn and tile edge for easy installation and feathering to wall/splash surface.
- "V" creased drainboards for positive drainage.

Mechanical:

- Water supply is $\frac{1}{2}$ (13mm) IPS for hot and cold lines.
- Faucet holes are 1½" (29mm) punched on 8" (203mm) centers; two sets of faucet holes are punched where indicated on chart (back page).
- Basket-type waste drain included fits sink bowls'
 3½" (89mm) opening and features 1½" (38mm) outlet.

Certifications / Approvals









EG20.25 Rev. 09/22




Item No.:	
Project No.:	
S.I.S. No.:	


414 Series Coved Corner Three-Compartment Sinks







	Overall wid	iths		—	——A——→ -— B —>
bowl size <u>Dimension A</u>				3″	5"1 1 1
in.	mm	in.	mm	76mm	127mm 🖟 9.5~
20" x 16"	508 x 406	27½"	699		1 241mm
24" x 18"	610 x 457	31¾"	807	1 1	
22" x 22"	559 x 559	29¾"	756	1 1	
24" x 24"	610 x 610	31¾″	807	13.5 <i>"</i> 343mm	44″ 1118mm
Drain	location fo	r rough	ı-in	37.5"	39"
bowl size Dimension B		953mm	991mm		
in.	mm	in.	mm		'
20" x 16"	508 x 406	14"	357		
24" x 18"	610 x 457	16″	406	 -	
22" x 22"	559 x 559	15"	381	9.75″	
24" x 24"	610 x 610	16″	406	248mm	J









	BOWL DIMENSIONS width length			DRAINBOARD length			OVERALL DIMENSIONS width length				weight		
model #	in.	mm	in.	mm	quantity	in.	mm	in.	mm	in.	mm	lbs.	kg
414-16-3	20″	508	16″	406	0		-	27½"	699	58¾"	1492	165	74.8
414-16-3-18R or L	20″	508	16″	406	1	18″	457	27½"	699	74%"	1889	170	77.1
414-16-3-18	20″	508	16″	406	2	18″	457	27½″	699	90″	2286	175	79.4
414-16-3-24R or L	20″	508	16"	406	1	24"	610	27½"	699	80%"	2042	190	86.2
414-16-3-24	20″	508	16″	406	2	24"	610	27½"	699	102"	2591	204	92.5
414-18-3*	24"	610	18″	457	0		-	31¾″	807	65½″	1664	167	75.8
414-18-3-18R or L*	24"	610	18″	457	1	18″	457	31¾″	807	80¾"	2051	206	93.4
414-18-3-18*	24"	610	18″	457	2	18″	457	31¾"	807	96″	2438	224	101.6
414-18-3-24R or L*	24"	610	18″	457	1	24"	610	31¾"	807	86¾"	2203	228	103.4
414-18-3-24*	24″	610	18″	457	2	24"	610	31¾″	807	108″	2743	232	105.2
414-22-3*	22"	559	22″	559	0		-	29¾"	756	77½″	1969	170	77.1
414-22-3-18R or L*	22"	559	22"	559	1	18″	457	29¾"	756	93"	2362	224	101.6
414-22-3-18*	22″	559	22"	559	2	18″	457	29¾"	756	108½"	2756	231	104.8
414-22-3-24R or L*	22"	559	22"	559	1	24"	610	29¾"	756	99"	2515	235	106.6
414-22-3-24*	22″	559	22"	559	2	24"	610	29¾″	756	120½"	3061	239	108.4
414-24-3*	24"	610	24"	610	0		-	31¾"	807	83½"	2121	175	79.4
414-24-3-18R or L*	24"	610	24"	610	1	18″	457	31¾"	807	98¾"	2508	226	102.5
414-24-3-18*	24"	610	24"	610	2	18″	457	31¾"	807	114"	2896	249	113.0
414-24-3-24R or L*	24″	610	24"	610	1	24"	610	31¾″	807	104¾"	2661	250	113.4
414-24-3-24*	24″	610	24″	610	2	24″	610	31¾″	807	126″	3200	260	117.9

^{*} Features two sets of faucet holes.

EAGLE GROUP

100 Industrial Boulevard, Clayton, DE 19938-8903 USA Phone: 302-653-3000 or 800-441-8440 • Fax: 302-653-2065 www.eaglegrp.com • www.eaglegrpnews.com • www.eaglemhc.com

Printed in U.S.A. ©2022 by Eagle Group

Rev. 09/22